



El blog de Neonigma

Manual de código

Manual de código de Drupal generado automáticamente con un script en Bash

Autor:

- El blog de Neonigma
- <http://www.nacho-alvarez.es>

Marzo 2010

Índice general

Índice de contenido	III
1. Carpeta drupal	1
1.1. Fichero cron.php	1
1.2. Fichero index.php	1
1.3. Fichero install.php	2
1.4. Fichero update.php	28
1.5. Fichero xmlrpc.php	43
2. Carpeta drupal/modules/aggregator	44
2.1. Fichero aggregator-feed-source.tpl.php	44
2.2. Fichero aggregator-item.tpl.php	45
2.3. Fichero aggregator-summary-items.tpl.php	46
2.4. Fichero aggregator-summary-item.tpl.php	46
2.5. Fichero aggregator-wrapper.tpl.php	47
3. Carpeta drupal/modules/block	48
3.1. Fichero block-admin-display-form.tpl.php	48
4. Carpeta drupal/modules/book	50
4.1. Fichero book-all-books-block.tpl.php	50
4.2. Fichero book-export-html.tpl.php	50
4.3. Fichero book-navigation.tpl.php	52
4.4. Fichero book-node-export-html.tpl.php	53
5. Carpeta drupal/modules/comment	55
5.1. Fichero comment-folded.tpl.php	55
5.2. Fichero comment.tpl.php	55
5.3. Fichero comment-wrapper.tpl.php	56
6. Carpeta drupal/modules/forum	58
6.1. Fichero forum-icon.tpl.php	58
6.2. Fichero forum-list.tpl.php	58

6.3. Fichero forums.tpl.php	60
6.4. Fichero forum-submitted.tpl.php	61
6.5. Fichero forum-topic-list.tpl.php	61
6.6. Fichero forum-topic-navigation.tpl.php	63
7. Carpeta drupal/modules/node	65
7.1. Fichero node.tpl.php	65
8. Carpeta drupal/modules/poll	67
8.1. Fichero poll-bar-block.tpl.php	67
8.2. Fichero poll-bar.tpl.php	67
8.3. Fichero poll-results-block.tpl.php	68
8.4. Fichero poll-results.tpl.php	69
8.5. Fichero poll-vote.tpl.php	69
9. Carpeta drupal/modules/profile	71
9.1. Fichero profile-block.tpl.php	71
9.2. Fichero profile-listing.tpl.php	72
9.3. Fichero profile-wrapper.tpl.php	73
10.Carpeta drupal/modules/search	75
10.1. Fichero search-block-form.tpl.php	75
10.2. Fichero search-results.tpl.php	76
10.3. Fichero search-result.tpl.php	76
10.4. Fichero search-theme-form.tpl.php	78
11.Carpeta drupal/modules/system	80
11.1. Fichero block.tpl.php	80
11.2. Fichero box.tpl.php	81
11.3. Fichero maintenance-page.tpl.php	81
11.4. Fichero page.tpl.php	83
12.Carpeta drupal/modules/user	89
12.1. Fichero user-picture.tpl.php	89
12.2. Fichero user-profile-category.tpl.php	89
12.3. Fichero user-profile-item.tpl.php	90
12.4. Fichero user-profile.tpl.php	91
13.Carpeta drupal/sites/default	93
13.1. Fichero default.settings.php	93
13.2. Fichero settings.php	98

14. Carpeta drupal/themes/bluemarine	104
14.1. Fichero block.tpl.php	104
14.2. Fichero box.tpl.php	104
14.3. Fichero comment.tpl.php	104
14.4. Fichero node.tpl.php	105
14.5. Fichero page.tpl.php	105
15. Carpeta drupal/themes/garland	108
15.1. Fichero block.tpl.php	108
15.2. Fichero comment.tpl.php	108
15.3. Fichero maintenance-page.tpl.php	109
15.4. Fichero node.tpl.php	111
15.5. Fichero page.tpl.php	112
15.6. Fichero template.php	114
16. Carpeta drupal/themes/pushbutton	117
16.1. Fichero block.tpl.php	117
16.2. Fichero box.tpl.php	117
16.3. Fichero comment.tpl.php	117
16.4. Fichero node.tpl.php	118
16.5. Fichero page.tpl.php	118

Capítulo 1

Carpetas drupal

1.1. Fichero cron.php

```
1 <?php
// $Id: cron.php, v 1.36 2006/08/09 07:42:55 dries Exp $
2
3 /**
 * @file
4 * Handles incoming requests to fire off regularly-scheduled tasks (...  

5 * cron jobs).
6 */
7
8 include_once './includes/bootstrap.inc';
9 drupal_bootstrap(DRUPAL_BOOTSTRAP_FULL);
10 drupal_cron_run();
11
```

1.2. Fichero index.php

```
<?php
// $Id: index.php, v 1.94 2007/12/26 08:46:48 dries Exp $
1
2 /**
 * @file
3 * The PHP page that serves all page requests on a Drupal installation...
4 *
5 * The routines here dispatch control to the appropriate handler, ...
6 * which then
7 * prints the appropriate page.
8 *
9 * All Drupal code is released under the GNU General Public License.
10 * See COPYRIGHT.txt and LICENSE.txt.
11 */
12
13 require_once './includes/bootstrap.inc';
14 drupal_bootstrap(DRUPAL_BOOTSTRAP_FULL);
15
16 $return = menu_execute_active_handler();
```

```

19 // Menu status constants are integers; page content is a string.
if (is_int($return)) {
  switch ($return) {
    case MENU_NOT_FOUND:
      drupal_not_found();
      break;
    case MENU_ACCESS_DENIED:
      drupal_access_denied();
      break;
    case MENU_SITE_OFFLINE:
      drupal_site_offline();
      break;
  }
}
34 elseif (isset($return)) {
  // Print any value (including an empty string) except NULL or ...
  // undefined:
  print theme('page', $return);
}
39 drupal_page_footer();

```

1.3. Fichero install.php

```

1 <?php
// $Id: install.php, v 1.113.2.10 2010/03/01 09:36:01 goba Exp $
require_once './includes/install.inc';

6 define('MAINTENANCE_MODE', 'install');

/**
 * The Drupal installation happens in a series of steps. We begin by ...
 * verifying
 * that the current environment meets our minimum requirements. We ...
 * then go
11 * on to verify that settings.php is properly configured. From there ...
 * we
 * connect to the configured database and verify that it meets our ...
 * minimum
 * requirements. Finally we can allow the user to select an ...
 * installation
 * profile and complete the installation process.
 *
16 * @param $phase
 *   The installation phase we should proceed to.
 */
function install_main() {
  require_once './includes/bootstrap.inc';
21  drupal_bootstrap(DRUPAL_BOOTSTRAP_CONFIGURATION);
}

```

```

// This must go after drupal_bootstrap(), which unsets globals!
global $profile, $install_locale, $conf;

26 require_once './modules/system/system.install';
require_once './includes/file.inc';

// Ensure correct page headers are sent (e.g. caching)
drupal_page_header();

31 // Set up $language, so t() caller functions will still work.
drupal_init_language();

// Load module basics (needed for hook invokes).
36 include_once './includes/module.inc';
$module_list['system']['filename'] = 'modules/system/system.module';
$module_list['filter']['filename'] = 'modules/filter/filter.module';
module_list(TRUE, FALSE, FALSE, $module_list);
drupal_load('module', 'system');
drupal_load('module', 'filter');

// Install profile chosen, set the global immediately.
// This needs to be done before the theme cache gets
// initialized in drupal_maintenance_theme().
46 if (!empty($_GET['profile'])) {
    $profile = preg_replace('/[^a-zA-Z_0-9]/', '', $_GET['profile']);
}

51 // Set up theme system for the maintenance page.
drupal_maintenance_theme();

// Check existing settings.php.
$verify = install_verify_settings();

56 if ($verify) {
    // Since we have a database connection, we use the normal cache ...
    // system.
    // This is important, as the installer calls into the Drupal ...
    // system for
    // the clean URL checks, so we should maintain the cache properly.
    require_once './includes/cache.inc';
    $conf['cache_inc'] = './includes/cache.inc';

    // Establish a connection to the database.
    require_once './includes/database.inc';
    db_set_active();

66    // Check if Drupal is installed.
    $task = install_verify_drupal();
    if ($task == 'done') {
        install_already_done_error();
    }
}
else {
}

```

```

// Since no persistent storage is available yet, and functions ...
// that check
// for cached data will fail, we temporarily replace the normal ...
// cache
76 // system with a stubbed-out version that short-circuits the ...
// actual
// caching process and avoids any errors.
require_once './includes/cache-install.inc';
$conf['cache_inc'] = './includes/cache-install.inc';

81 $task = NULL;
}

// No profile was passed in GET, ask the user.
if (empty($_GET['profile'])) {
    if ($profile = install_select_profile()) {
        install_goto("install.php?profile=$profile");
    }
    else {
        install_no_profile_error();
    }
}

91

// Load the profile.
require_once "./profiles/$profile/$profile.profile";
96

// Locale selection
if (!empty($_GET['locale'])) {
    $install_locale = preg_replace('/[^a-zA-Z_0-9\-\_]/', '', $_GET['...
    locale']);
}
101 elseif (($install_locale = install_select_locale($profile)) !== ...
    FALSE) {
    install_goto("install.php?profile=$profile&locale=$install_locale"...
);
}

106

// Tasks come after the database is set up
if (!$task) {
    global $db_url;

    if (!$verify && !empty($db_url)) {
        // Do not install over a configured settings.php.
        install_already_done_error();
    }

    // Check the installation requirements for Drupal and this profile...
    install_check_requirements($profile, $verify);

    111

    // Verify existence of all required modules.
    $modules = drupal_verify_profile($profile, $install_locale);
}

```

```

    // If any error messages are set now, it means a requirement ...
121   $messages = drupal_set_message();
    if (!empty($messages['error'])) {
      install_task_list('requirements');
      drupal_set_title(st('Requirements problem'));
      print theme('install_page', '');
      exit;
    }

    // Change the settings.php information if verification failed ...
earlier.
    // Note: will trigger a redirect if database credentials change.
131   if (!$verify) {
      install_change_settings($profile, $install_locale);
    }

    // Install system.module.
136   drupal_install_system();
    // Save the list of other modules to install for the 'profile-
install'
    // task. variable_set() can be used now that system.module is ...
installed
    // and drupal is bootstrapped.
    variable_set('install_profile_modules', array_diff($modules, array...
('system')));
141 }

    // The database is set up, turn to further tasks.
    install_tasks($profile, $task);
}

146 /**
 * Verify if Drupal is installed.
 */
function install_verify_drupal() {
  // Read the variable manually using the @ so we don't trigger an ...
  // error if it fails.
  $result = @db_query("SELECT value FROM {variable} WHERE name = '%s'...
  , 'install_task');
  if ($result) {
    return unserialize(db_result($result));
  }
156 }

/**
 * Verify existing settings.php
 */
161 function install_verify_settings() {
  global $db_prefix, $db_type, $db_url;

  // Verify existing settings (if any).
  if (!empty($db_url)) {
    // We need this because we want to run form_get_errors.

```

```

    include_once './includes/form.inc';

    $url = parse_url(is_array($db_url) ? $db_url['default'] : $db_url);
    $db_user = urldecode($url['user']);
    $db_pass = isset($url['pass']) ? urldecode($url['pass']) : NULL;
    $db_host = urldecode($url['host']);
    $db_port = isset($url['port']) ? urldecode($url['port']) : '';
    $db_path = ltrim(urldecode($url['path']), '/');
    $settings_file = './conf_path(FALSE, TRUE) . settings.php';

171    $form_state = array();
    _install_settings_form_validate($db_prefix, $db_type, $db_user, ...
    $db_pass, $db_host, $db_port, $db_path, $settings_file, ...
    $form_state);
    if (!form_get_errors()) {
        return TRUE;
    }
181    }
    return FALSE;
}

186 /**
 * Configure and rewrite settings.php.
 */
function install_change_settings($profile = 'default', $install_locale...
    = '') {
    global $db_url, $db_type, $db_prefix;

191    $url = parse_url(is_array($db_url) ? $db_url['default'] : $db_url);
    $db_user = isset($url['user']) ? urldecode($url['user']) : '';
    $db_pass = isset($url['pass']) ? urldecode($url['pass']) : '';
    $db_host = isset($url['host']) ? urldecode($url['host']) : '';
196    $db_port = isset($url['port']) ? urldecode($url['port']) : '';
    $db_path = ltrim(urldecode($url['path']), '/');
    $conf_path = './conf_path(FALSE, TRUE)';
    $settings_file = $conf_path . settings.php';

201    // We always need this because we want to run form_get_errors.
    include_once './includes/form.inc';
    install_task_list('database');

    $output = drupal_get_form('install_settings_form', $profile, ...
        $install_locale, $settings_file, $db_url, $db_type, $db_prefix, ...
        $db_user, $db_pass, $db_host, $db_port, $db_path);
206    drupal_set_title(st('Database configuration'));
    print theme('install_page', $output);
    exit;
}

211 /**
 * Form API array definition for install_settings.
 */

```

```

function install_settings_form(&$form_state, $profile, $install_locale ...
    , $settings_file, $db_url, $db_type, $db_prefix, $db_user, ...
    $db_pass, $db_host, $db_port, $db_path) {
216  if (empty($db_host)) {
    $db_host = 'localhost';
  }
  $db_types = drupal_detect_database_types();

221 // If both 'mysql' and 'mysqli' are available, we disable 'mysql':
if (isset($db_types['mysqli'])) {
  unset($db_types['mysql']);
}

226 if (count($db_types) == 0) {
  $form['no_db_types'] = array(
    '#value' => st('Your web server does not appear to support any ...
      common database types. Check with your hosting provider to see if ...
      they offer any databases that <a href="@drupal-databases">Drupal ...
      supports</a>.', array('@drupal-databases' => 'http://drupal.org/...
        node/270#database')) ,
  );
}
231 else {
  $form['basic_options'] = array(
    '#type' => 'fieldset',
    '#title' => st('Basic options'),
    '#description' => '<p>' . st('To set up your @drupal database, ...
      enter the following information.', array('@drupal' => ...
        drupal_install_profile_name())) . '</p>',
  );
236

if (count($db_types) > 1) {
  $form['basic_options']['db_type'] = array(
    '#type' => 'radios',
    '#title' => st('Database type'),
    '#required' => TRUE,
    '#options' => $db_types,
    '#default_value' => ($db_type ? $db_type : current($db_types)) ...
  ,
    '#description' => st('The type of database your @drupal data ...
      will be stored in.', array('@drupal' => ...
        drupal_install_profile_name())),
  );
241
  $db_path_description = st('The name of the database your @drupal...
    data will be stored in. It must exist on your server before ...
    @drupal can be installed.', array('@drupal' => ...
      drupal_install_profile_name()));
}
246
else {
  if (count($db_types) == 1) {
    $db_types = array_values($db_types);
    $form['basic_options']['db_type'] = array(
      '#type' => 'hidden',
      '#value' => $db_types[0],
251
  }
}

```

```

256     );
257     $db_path_description = st('The name of the %db_type database ...
258     your @drupal data will be stored in. It must exist on your server ...
259     before @drupal can be installed.', array('%db_type' => $db_types...
260     [0], '@drupal' => drupal_install_profile_name()));
261     }
262   }

263   // Database name
264   $form['basic_options']['db_path'] = array(
265     '#type' => 'textfield',
266     '#title' => st('Database name'),
267     '#default_value' => $db_path,
268     '#size' => 45,
269     '#required' => TRUE,
270     '#description' => $db_path_description
271   );

272   // Database username
273   $form['basic_options']['db_user'] = array(
274     '#type' => 'textfield',
275     '#title' => st('Database username'),
276     '#default_value' => $db_user,
277     '#size' => 45,
278     '#required' => TRUE,
279   );

280   // Database password
281   $form['basic_options']['db_pass'] = array(
282     '#type' => 'password',
283     '#title' => st('Database password'),
284     '#default_value' => $db_pass,
285     '#size' => 45,
286   );

287   $form['advanced_options'] = array(
288     '#type' => 'fieldset',
289     '#title' => st('Advanced options'),
290     '#collapsible' => TRUE,
291     '#collapsed' => TRUE,
292     '#description' => st("These options are only necessary for some ...
293     sites. If you're not sure what you should enter here, leave the ...
294     default settings or check with your hosting provider.")
295   );

296   // Database host
297   $form['advanced_options']['db_host'] = array(
298     '#type' => 'textfield',
299     '#title' => st('Database host'),
300     '#default_value' => $db_host,
301     '#size' => 45,
302     // Hostnames can be 255 characters long.
303     '#maxlength' => 255,
304     '#required' => TRUE,
305   );

```

```

    '#description' => st('If your database is located on a different...
server, change this.'),
);

306
// Database port
$form['advanced_options']['db_port'] = array(
  '#type' => 'textfield',
  '#title' => st('Database port'),
  '#default_value' => $db_port,
  '#size' => 45,
  // The maximum port number is 65536, 5 digits.
  '#maxlength' => 5,
  '#description' => st('If your database server is listening to a ...
non-standard port, enter its number.'),
);

316

// Table prefix
$prefix = ($profile == 'default') ? 'drupal_' : $profile . '_';
$form['advanced_options']['db_prefix'] = array(
  '#type' => 'textfield',
  '#title' => st('Table prefix'),
  '#default_value' => $db_prefix,
  '#size' => 45,
  '#description' => st('If more than one application will be ...
sharing this database, enter a table prefix such as %prefix for ...
your @drupal site here.', array('@drupal' => ...
drupal_install_profile_name(), '%prefix' => $prefix)),
);

326

$form['save'] = array(
  '#type' => 'submit',
  '#value' => st('Save and continue'),
);

331

$form['errors'] = array();
$form['settings_file'] = array('#type' => 'value', '#value' => ...
$settings_file);
$form['_db_url'] = array('#type' => 'value');
$form['#action'] = "install.php?profile=$profile".(...);
$install_locale ? "&locale=$install_locale" : '');
$form['#redirect'] = FALSE;
}

336
return $form;
}

341
/**
 * Form API validate for install_settings form.
 */
function install_settings_form_validate($form, &$amp;form_state) {
  global $db_url;
  _install_settings_form_validate($form_state['values']['db_prefix'], ...
  $form_state['values']['db_type'], $form_state['values']['db_user']...
  ], $form_state['values']['db_pass'], $form_state['values'][',...
db_host'], $form_state['values']['db_port'], $form_state['values']...
);
}

```

```

] [ 'db_path' ] , $form_state[ 'values' ][ 'settings_file' ] , $form_state , ...
$form) ;
}

/**
351 * Helper function for install_settings_validate .
*/
function _install_settings_form_validate($db_prefix , $db_type , ...
$db_user , $db_pass , $db_host , $db_port , $db_path , $settings_file ,
&$form_state , $form = NULL) {
global $db_url;

// Verify the table prefix
356 if (!empty($db_prefix) && is_string($db_prefix) && !preg_match('/^[_A...
-Za-z0-9_.]+\$/i' , $db_prefix)) {
  form_set_error('db_prefix' , st('The database table prefix you have...
  entered , %db_prefix , is invalid. The table prefix can only ...
  contain alphanumeric characters , periods , or underscores.' , array(... ...
  '%db_prefix' => $db_prefix)) , 'error');
}

361 if (!empty($db_port) && !is_numeric($db_port)) {
  form_set_error('db_port' , st('Database port must be a number.'));
}

// Check database type
366 if (!isset($form)) {
  $db_url = is_array($db_url) ? $db_url['default'] : $db_url;
  $db_type = substr($db_url , 0 , strpos($db_url , '://'));
}
$databases = drupal_detect_database_types();
371 if (!in_array($db_type , $databases)) {
  form_set_error('db_type' , st("In your %settings_file file you have...
  configured @drupal to use a %db_type server , however your PHP ...
  installation currently does not support this database type." , ...
  array('%settings_file' => $settings_file , '@drupal' => ...
  drupal_install_profile_name() , '%db_type' => $db_type)));
}
else {
  // Verify
376 $db_url = $db_type . '://'. urlencode($db_user) . ($db_pass ? ':' . ...
  urlencode($db_pass) : '') . '@'. ($db_host ? urlencode($db_host) : ...
  'localhost') . ($db_port ? ":" . $db_port : '') . '/'. urlencode(... ...
  $db_path);
  if (isset($form)) {
    form_set_value($form['_db_url'] , $db_url , $form_state);
  }
  $success = array();
}

381 $function = 'drupal_test_'.$db_type;
if (!$function($db_url , $success)) {
  if (isset($success['CONNECT'])) {
    form_set_error('db_type' , st('In order for Drupal to work , and...
    to continue with the installation process , you must resolve all ...'));
}

```

```

    permission issues reported above. We were able to verify that we ...
    have permission for the following commands: %commands. For more ...
    help with configuring your database server, see the <a href="http...
    ://drupal.org/node/258">Installation and upgrading handbook</a>. ...
    If you are unsure what any of this means you should probably ...
    contact your hosting provider.', array('%commands' => implode(...
    $success, ', ', '')));
386     }
387     else {
388         form_set_error('db_type', '');
389     }
390 }
391 }

/**
* Form API submit for install_settings form.
396 */
function install_settings_form_submit($form, &$form_state) {
    global $profile, $install_locale;

    // Update global settings array and save
401     $settings['db_url'] = array(
        'value' => $form_state['values']['_db_url'],
        'required' => TRUE,
    );
    $settings['db_prefix'] = array(
        'value' => $form_state['values']['db_prefix'],
        'required' => TRUE,
    );
    drupal_rewrite_settings($settings);

    // Continue to install profile step
411     install_goto("install.php?profile=$profile". ($install_locale ? "&...
        locale=$install_locale" : ''));
}

/**
416 * Find all .profile files.
*/
function install_find_profiles() {
    return file_scan_directory('./profiles', '\.profile$', array('.', '...
        ..', 'CVS'), 0, TRUE, 'name', 0);
}
421

/**
* Allow admin to select which profile to install.
*
* @return
*     The selected profile.
*/
426 function install_select_profile() {
    include_once './includes/form.inc';
}

```

```

431     $profiles = install_find_profiles();
432     // Don't need to choose profile if only one available.
433     if (sizeof($profiles) == 1) {
434         $profile = array_pop($profiles);
435         require_once $profile->filename;
436         return $profile->name;
437     }
438     elseif (sizeof($profiles) > 1) {
439         foreach ($profiles as $profile) {
440             if (!empty($_POST['profile']) && ($_POST['profile'] == $profile...
441             ->name)) {
442                 return $profile->name;
443             }
444         }
445     }
446
447     install_task_list('profile-select');
448
449     drupal_set_title(st('Select an installation profile'));
450     print theme('install_page', drupal_get_form('...
451     install_select_profile_form', $profiles));
452     exit;
453 }
454
455 /**
456 * Form API array definition for the profile selection form.
457 *
458 * @param $form_state
459 *   Array of metadata about state of form processing.
460 * @param $profile_files
461 *   Array of .profile files, as returned from file_scan_directory().
462 */
463 function install_select_profile_form(&$form_state, $profile_files) {
464     $profiles = array();
465     $names = array();
466
467     foreach ($profile_files as $profile) {
468         include_once($profile->filename);
469
470         // Load profile details and store them for later retrieval.
471         $function = $profile->name . '_profile_details';
472         if (function_exists($function)) {
473             $details = $function();
474         }
475         $profiles[$profile->name] = $details;
476
477         // Determine the name of the profile; default to file name if ...
478         // defined name
479         // is unspecified.
480         $name = isset($details['name']) ? $details['name'] : $profile->...
481         name;
482         $names[$profile->name] = $name;
483     }

```

```

481 // Display radio buttons alphabetically by human-readable name.
482 natcasesort($names);
483 foreach ($names as $profile => $name) {
484   $form['profile'][$name] = array(
485     '#type' => 'radio',
486     '#value' => 'default',
487     '#return_value' => $profile,
488     '#title' => $name,
489     '#description' => isset($profiles[$profile]['description']) ? ...
490       $profiles[$profile]['description'] : '',
491     '#parents' => array('profile'),
492   );
493 }
494 $form['submit'] = array(
495   '#type' => 'submit',
496   '#value' => st('Save and continue'),
497 );
498 return $form;
499 }

500 /**
501 * Find all .po files for the current profile.
502 */
503 function install_find_locales($profilename) {
504   $locales = file_scan_directory('..//profiles/' . $profilename . '/...
505     translations', '\.po$', array('.', '..', 'CVS'), 0, FALSE);
506   array_unshift($locales, (object) array('name' => 'en'));
507   return $locales;
508 }

509 /**
510 * Allow admin to select which locale to use for the current profile.
511 */
512 /**
513 * @return
514 *   The selected language.
515 */
516 function install_select_locale($profilename) {
517   include_once '..//includes/file.inc';
518   include_once '..//includes/form.inc';

519   // Find all available locales.
520   $locales = install_find_locales($profilename);

521   // If only the built-in (English) language is available,
522   // and we are using the default profile, inform the user
523   // that the installer can be localized. Otherwise we assume
524   // the user know what he is doing.
525   if (count($locales) == 1) {
526     if ($profilename == 'default') {
527       install_task_list('locale-select');
528       drupal_set_title(st('Choose language'));
529       if (!empty($_GET['localize'])) {
530         $output = '<p>' . st('With the addition of an appropriate ...');
531         translation package, this installer is capable of proceeding in ...');

```

```

another language of your choice. To install and use Drupal in a ...
language other than English:') . '</p>';
    $output .= '<ul><li>'. st('Determine if <a href="@translations...
" target="_blank">a translation of this Drupal version</a> is ...
available in your language of choice. A translation is provided ...
via a translation package; each translation package enables the ...
display of a specific version of Drupal in a specific language. ...
Not all languages are available for every version of Drupal.', ...
array('@translations' => 'http://drupal.org/project/translations')...
) . '</li>';
    $output .= '<li>'. st('If an alternative translation package ...
of your choice is available, download and extract its contents to ...
your Drupal root directory.') . '</li>';
    $output .= '<li>'. st('Return to choose language using the ...
second link below and select your desired language from the ...
displayed list. Reloading the page allows the list to ...
automatically adjust to the presence of new translation packages.')...
) . '</li>';
    $output .= '</ul><p>'. st('Alternatively, to install and use ...
Drupal in English, or to defer the selection of an alternative ...
language until after installation, select the first link below.') ...
. '</p>';
536   $output .= '<p>'. st('How should the installation continue?') ...
. '</p>';
    $output .= '<ul><li><a href="install.php?profile=' . ...
$filename . '&locale=en">'. st('Continue installation in ...
English') . '</a></li><li><a href="install.php?profile=' . ...
$filename . '">'. st('Return to choose a language') . '</a></li ...
></ul>';
}
else {
    $output = '<ul><li><a href="install.php?profile=' . ...
$filename . '&locale=en">'. st('Install Drupal in English') ...
. '</a></li><li><a href="install.php?profile=' . $filename . '&...
;localize=true">'. st('Learn how to install Drupal in other ...
languages') . '</a></li></ul>';
}
541   print theme('install_page', $output);
    exit;
}
// One language, but not the default profile, assume
// the user knows what he is doing.
546   return FALSE;
}
else {
    // Allow profile to pre-select the language, skipping the ...
selection.
551   $function = $filename . '_profile_details';
    if ($function_exists($function)) {
        $details = $function();
        if (isset($details['language'])) {
            foreach ($locales as $locale) {
                if ($details['language'] == $locale->name) {
556       return $locale->name;
}

```

```

        }
    }

561 }

if (!empty($_POST['locale'])) {
foreach ($locales as $locale) {
    if ($_POST['locale'] == $locale->name) {
        return $locale->name;
    }
}
}

566 }

571 install_task_list('locale-select');

drupal_set_title(st('Choose language'));
print theme('install_page', drupal_get_form('...
install_select_locale_form', $locales));
exit;
576 }

577 }

581 /**
 * Form API array definition for language selection.
 */
function install_select_locale_form(&$form_state, $locales) {
    include_once './includes/locale.inc';
    $languages = _locale_get_predefined_list();
    foreach ($locales as $locale) {
586     // Try to use verbose locale name
        $name = $locale->name;
        if (isset($languages[$name])) {
            $name = $languages[$name][0] . (isset($languages[$name][1]) ? ' ... '
                . st('@language'), array('@language' => $languages[$name][1])) : '';
        }
591     $form['locale'][$locale->name] = array(
        '#type' => 'radio',
        '#return_value' => $locale->name,
        '#default_value' => ($locale->name == 'en' ? TRUE : FALSE),
        '#title' => $name . ($locale->name == 'en' ? ' ' . st('(built-in)...') : ''),
        '#parents' => array('locale')
    );
596 }
    $form['submit'] = array(
        '#type' => 'submit',
        '#value' => st('Select language'),
    );
    return $form;
}

601 }

606 /**
 * Show an error page when there are no profiles available.
*/

```

```

/*
function install_no_profile_error() {
  install_task_list('profile-select');
  drupal_set_title(st('No profiles available'));
  print theme('install_page', '<p>'. st('We were unable to find any ...
    installer profiles. Installer profiles tell us what modules to ...
    enable and what schema to install in the database. A profile is ...
    necessary to continue with the installation process.') . '</p>');
  exit;
}

616 /**
 * Show an error page when Drupal has already been installed.
 */
function install_already_done_error() {
621   global $base_url;

  drupal_set_title(st('Drupal already installed'));
  print theme('install_page', st('<ul><li>To start over, you must ...
    empty your existing database.</li><li>To install to a different ...
    database, edit the appropriate <em>settings.php</em> file in the <...
    em>sites </em> folder.</li><li>To upgrade an existing installation, ...
    proceed to the <a href="@base-url/update.php">update script</a...
    >.</li><li>View your <a href="@base-url">existing site</a>.</li><...
    ul>', array('@base-url' => $base_url)));
  exit;
}

626 */

631 /**
 * Tasks performed after the database is initialized.
 */
function install_tasks($profile, $task) {
  global $base_url, $install_locale;

  // Bootstrap newly installed Drupal, while preserving existing ...
  // messages.
  $messages = isset($_SESSION['messages']) ? $_SESSION['messages'] : '';
  drupal_bootstrap(DRUPAL_BOOTSTRAP_FULL);
  $_SESSION['messages'] = $messages;

  // URL used to direct page requests.
  $url = $base_url . '/install.php?locale=' . $install_locale . '&profile...
  =' . $profile;

641  // Build a page for final tasks.
  if (empty($task)) {
    variable_set('install_task', 'profile-install');
    $task = 'profile-install';
  }

646  // We are using a list of if constructs here to allow for
  // passing from one task to the other in the same request.

```

```

651 // Install profile modules.
652 if ($task == 'profile-install') {
653   $modules = variable_get('install_profile_modules', array());
654   $files = module_rebuild_cache();
655   variable_del('install_profile_modules');
656   $operations = array();
657   foreach ($modules as $module) {
658     $operations[] = array('_install_module_batch', array($module, ...
659       $files[$module]->info['name']));
660   }
661   $batch = array(
662     'operations' => $operations,
663     'finished' => '_install_profile_batch_finished',
664     'title' => st('Installing @drupal', array('@drupal' => ...
665       drupal_install_profile_name())),
666     'error_message' => st('The installation has encountered an error...
667     .'),
668   );
669   // Start a batch, switch to 'profile-install-batch' task. We need ...
670   // to
671   // set the variable here, because batch_process() redirects.
672   variable_set('install_task', 'profile-install-batch');
673   batch_set($batch);
674   batch_process($url, $url);
675 }
676 // We are running a batch install of the profile's modules.
677 // This might run in multiple HTTP requests, constantly redirecting
678 // to the same address, until the batch finished callback is invoked
679 // and the task advances to 'locale-initial-import'.
680 if ($task == 'profile-install-batch') {
681   include_once 'includes/batch.inc';
682   $output = _batch_page();
683 }
684 // Import interface translations for the enabled modules.
685 if ($task == 'locale-initial-import') {
686   if (!empty($install_locale) && ($install_locale != 'en')) {
687     include_once 'includes/locale.inc';
688     // Enable installation language as default site language.
689     locale_add_language($install_locale, NULL, NULL, NULL, NULL, ...
690     NULL, 1, TRUE);
691     // Collect files to import for this language.
692     $batch = locale_batch_by_language($install_locale, '...
693     _install_locale_initial_batch_finished');
694     if (!empty($batch)) {
695       // Remember components we cover in this batch set.
696       variable_set('install_locale_batch_components', $batch['#...
697       components']);
698       // Start a batch, switch to 'locale-batch' task. We need to
699       // set the variable here, because batch_process() redirects.
700       variable_set('install_task', 'locale-initial-batch');
701       batch_set($batch);
702       batch_process($url, $url);

```

```

        }
    }
    // Found nothing to import or not foreign language, go to next ...
    // task.
    $task = 'configure';
701 if ($task == 'locale-initial-batch') {
    include_once 'includes/batch.inc';
    include_once 'includes/locale.inc';
    $output = _batch_page();
706 }

if ($task == 'configure') {
    if (variable_get('site_name', FALSE) || variable_get('site_mail', ...
    FALSE)) {
        // Site already configured: This should never happen, means re-...
        // running
        // the installer, possibly by an attacker after the '...
        install_task' variable
        // got accidentally blown somewhere. Stop it now.
        install_already_done_error();
    }
    $form = drupal_get_form('install_configure_form', $url);
716 if (!variable_get('site_name', FALSE) && !variable_get('site_mail'...
    , FALSE)) {
        // Not submitted yet: Prepare to display the form.
        $output = $form;
        drupal_set_title(st('Configure site'));
721
        // Warn about settings.php permissions risk
        $settings_dir = './' . conf_path();
        $settings_file = $settings_dir . '/settings.php';
        if (!drupal_verify_install_file($settings_file, FILE_EXIST|...
        FILE_READABLE|FILE_NOT_WRITABLE) || !drupal_verify_install_file(...$settings_dir, FILE_NOT_WRITABLE, 'dir')) {
726            drupal_set_message(st('All necessary changes to %dir and %file...
            have been made, so you should remove write permissions to them ...
            now in order to avoid security risks. If you are unsure how to do ...
            so, please consult the <a href="@handbook_url">on-line handbook</a...
            >.', array('%dir' => $settings_dir, '%file' => $settings_file, '@...
            handbook_url' => 'http://drupal.org/getting-started')), 'error');
        }
        else {
            drupal_set_message(st('All necessary changes to %dir and %file...
            have been made. They have been set to read-only for security.', ...
            array('%dir' => $settings_dir, '%file' => $settings_file)));
        }
731
        // Add JavaScript validation.
        user_password_dynamic_validation();
        drupal_add_js(drupal_get_path('module', 'system') . '/system.js',...
        'module');
    }
}

```

```

    // We add these strings as settings because JavaScript ...
736   translation does not
    // work on install time.
    drupal_add_js(array('copyFieldValue' => array('edit-site-mail' ...
=> array('edit-account-mail')), 'cleanURL' => array('success' => ...
st('Your server has been successfully tested to support this ...
feature.'), 'failure' => st('Your system configuration does not ...
currently support this feature. The <a href="http://drupal.org/...
node/15365">handbook page on Clean URLs</a> has additional ...
troubleshooting information.'), 'testing' => st('Testing clean ...
URLs...'))), 'setting');
    drupal_add_js(
// Global Killswitch
if (Drupal.jsEnabled) {
  $(document).ready(function() {
    Drupal.cleanURLsInstallCheck();
    Drupal.setDefaultTimezone();
  });
}, 'inline');
746   // Build menu to allow clean URL check.
    menu_rebuild();
}

else {
  $task = 'profile';
}
}

// If found an unknown task or the 'profile' task, which is
756 // reserved for profiles, hand over the control to the profile,
// so it can run any number of custom tasks it defines.
if (!in_array($task, install_reserved_tasks())) {
  $function = $profile . '_profile_tasks';
  if (function_exists($function)) {
761    // The profile needs to run more code, maybe even more tasks.
    // $task is sent through as a reference and may be changed!
    $output = $function($task, $url);
  }

766 // If the profile doesn't move on to a new task we assume
// that it is done.
if ($task == 'profile') {
  $task = 'profile-finished';
}
771 }

// Profile custom tasks are done, so let the installer regain
// control and proceed with importing the remaining translations.
if ($task == 'profile-finished') {
  if (!empty($install_locale) && ($install_locale != 'en')) {
    include_once 'includes/locale.inc';
    // Collect files to import for this language. Skip components
    // already covered in the initial batch set.
}

```

```

$batch = locale_batch_by_language($install_locale, '...
781   _install_locale_remaining_batch_finished', variable_get('...
   install_locale_batch_components', array()));
    // Remove temporary variable.
    variable_del('install_locale_batch_components');
    if (!empty($batch)) {
        // Start a batch, switch to 'locale-remaining-batch' task. We ...
        need to
        // set the variable here, because batch_process() redirects.
786        variable_set('install_task', 'locale-remaining-batch');
        batch_set($batch);
        batch_process($url, $url);
    }
}
// Found nothing to import or not foreign language, go to next ...
791 task.
$task = 'finished';
}
if ($task == 'locale-remaining-batch') {
    include_once 'includes/batch.inc';
796    include_once 'includes/locale.inc';
    $output = _batch_page();
}

// Display a 'finished' page to user.
801 if ($task == 'finished') {
    drupal_set_title(st('@drupal installation complete', array('...
    @drupal' => drupal_install_profile_name())));
    $messages = drupal_set_message();
    $output = '<p>' . st('Congratulations, @drupal has been ...'
    successfully installed.', array('@drupal' => ...
    drupal_install_profile_name())) . '</p>';
    $output .= '<p>' . (isset($messages['error']) ? st('Please review ...'
    the messages above before continuing on to <a href="@url">your new...
    site </a>.', array('@url' => url(''))) : st('You may now visit <a ...
    href="@url">your new site </a>.', array('@url' => url('')))) . '</p>...
    ';
    $task = 'done';
}

// The end of the install process. Remember profile used.
if ($task == 'done') {
    // Rebuild menu to get content type links registered by the ...
811    profile,
    // and possibly any other menu items created through the tasks.
    menu_rebuild();

    // Register actions declared by any modules.
816    actions_synchronize();

    // Randomize query-strings on css/js files, to hide the fact that
    // this is a new install, not upgraded yet.
    _drupal_flush_css_js();
821

```

```

        variable_set('install_profile', $profile);
    }

    // Set task for user, and remember the task in the database.
826   install_task_list($task);
    variable_set('install_task', $task);

    // Output page, if some output was required. Otherwise it is ...
    // possible
    // that we are printing a JSON page and theme output should not be ...
    // there.
831   if (isset($output)) {
        print theme('maintenance_page', $output);
    }
}

836 /**
 * Batch callback for batch installation of modules.
 */
function _install_module_batch($module, $module_name, &$context) {
    _drupal_install_module($module);
    // We enable the installed module right away, so that the module ...
    // will be
    // loaded by drupal_bootstrap in subsequent batch requests, and ...
    // other
    // modules possibly depending on it can safely perform their ...
    // installation
    // steps.
    module_enable(array($module));
    $context['results'][] = $module;
    $context['message'] = st('Installed %module module.', array(
        '%module' => $module_name));
}

851 /**
 * Finished callback for the modules install batch.
 *
 * Advance installer task to language import.
 */
function _install_profile_batch_finished($success, $results) {
856   variable_set('install_task', 'locale-initial-import');
}

861 /**
 * Finished callback for the first locale import batch.
 *
 * Advance installer task to the configure screen.
 */
function _install_locale_initial_batch_finished($success, $results) {
866   variable_set('install_task', 'configure');
}

881 /**
 * Finished callback for the second locale import batch.
 */

```

```

871   *
871   * Advance installer task to the finished screen.
871   */
871   function _install_locale_remaining_batch_finished($success, $results) ...
871   {
871     variable_set('install_task', 'finished');
871   }
876 /**
876  * The list of reserved tasks to run in the installer.
876  */
876  function install_reserved_tasks() {
881    return array('configure', 'profile-install', 'profile-install-batch'...
881      , 'locale-initial-import', 'locale-initial-batch', 'profile-...
881      finished', 'locale-remaining-batch', 'finished', 'done');
881  }
886 /**
886  * Check installation requirements and report any errors.
886  */
886  function install_check_requirements($profile, $verify) {
886
886    // If Drupal is not set up already, we need to create a settings ...
886    file.
886    if (!$verify) {
889      $writable = FALSE;
889      $conf_path = './'. conf_path(FALSE, TRUE);
889      $settings_file = $conf_path .'/settings.php';
889      $file = $conf_path;
889      $exists = FALSE;
889
896    // Verify that the directory exists.
896    if (drupal_verify_install_file($conf_path, FILE_EXIST, 'dir')) {
896      // Check to make sure a settings.php already exists.
896      $file = $settings_file;
896      if (drupal_verify_install_file($settings_file, FILE_EXIST)) {
896        $exists = TRUE;
896        // If it does, make sure it is writable.
896        $writable = drupal_verify_install_file($settings_file, ...
896          FILE_READABLE|FILE_WRITABLE);
896      }
896    }
896    if (!$exists) {
896      drupal_set_message(st('The @drupal installer requires that you ...
896      create a settings file as part of the installation process.
<ol>
<li>Copy the %default_file file to %file.</li>
<li>Change file permissions so that it is writable by the web server. ...
896      If you are unsure how to grant file permissions, please consult ...
896      the <a href="@handbook_url">on-line handbook</a>.</li>
896</ol>
More details about installing Drupal are available in INSTALL.txt.', ...
896      array('@drupal' => drupal_install_profile_name(), '%file' => $file ...
896      , '%default_file' => $conf_path .'/default.settings.php', '...
896      @handbook_url' => 'http://drupal.org/server-permissions')), 'error...

```

```

        ')
    }
    elseif (!\$writable) {
        drupal_set_message(st('The @drupal installer requires write ...
permissions to %file during the installation process. If you are ...
unsure how to grant file permissions, please consult the <a href="...
@handbook_url>on-line handbook</a>.'), array('@drupal' => ...
drupal_install_profile_name(), '%file' => $file, '@handbook_url' ...
=> 'http://drupal.org/server-permissions')), 'error');
    }
}

// Check the other requirements.
$requirements = drupal_check_profile($profile);
$severity = drupal_requirements_severity($requirements);

// If there are issues, report them.
if ($severity == REQUIREMENT_ERROR) {

    foreach ($requirements as $requirement) {
        if (isset($requirement['severity']) && $requirement['severity'] ...
== REQUIREMENT_ERROR) {
            $message = $requirement['description'];
            if (isset($requirement['value'])) && $requirement['value']) {
                $message .= ' (' . st('Currently using !item !version', array...
('!item' => $requirement['title'], '!version' => $requirement['...
value'])) . ')';
            }
            drupal_set_message($message, 'error');
        }
    }
}

if ($severity == REQUIREMENT_WARNING) {

    foreach ($requirements as $requirement) {
        if (isset($requirement['severity']) && $requirement['severity'] ...
== REQUIREMENT_WARNING) {
            $message = $requirement['description'];
            if (isset($requirement['value'])) && $requirement['value']) {
                $message .= ' (' . st('Currently using !item !version', array...
('!item' => $requirement['title'], '!version' => $requirement['...
value'])) . ')';
            }
            drupal_set_message($message, 'warning');
        }
    }
}

/**
 * Add the installation task list to the current page.
 */
function install_task_list($active = NULL) {
    // Default list of tasks.
}

```

```

956 $tasks = array(
957   'profile-select' => st('Choose profile'),
958   'locale-select' => st('Choose language'),
959   'requirements' => st('Verify requirements'),
960   'database' => st('Set up database'),
961   'profile-install-batch' => st('Install profile'),
962   'locale-initial-batch' => st('Set up translations'),
963   'configure' => st('Configure site'),
964 );
965
966 $profiles = install_find_profiles();
967 $profile = isset($_GET['profile']) && isset($profiles[$_GET['profile']]) ? $_GET['profile'] : '';
968 $locales = install_find_locales($profile);
969
970 // If we have only one profile, remove 'Choose profile'
971 // and rename 'Install profile'.
972 if (count($profiles) == 1) {
973   unset($tasks['profile-select']);
974   $tasks['profile-install-batch'] = st('Install site');
975 }
976
977 // Add tasks defined by the profile.
978 if ($profile) {
979   $function = $profile . '_profile_task_list';
980   if (function_exists($function)) {
981     $result = $function();
982     if (is_array($result)) {
983       $tasks += $result;
984     }
985   }
986
987 if (count($locales) < 2 || empty($_GET['locale']) || $_GET['locale'] ==
988 == 'en') {
989   // If not required, remove translation import from the task list.
990   unset($tasks['locale-initial-batch']);
991 }
992 else {
993   // If required, add remaining translations import task.
994   $tasks += array('locale-remaining-batch' => st('Finish ...
995   translations')));
996 }
997
998 // Add finished step as the last task.
999 $tasks += array(
1000   'finished' => st('Finished')
1001 );
1002
1003 // Let the theming function know that 'finished' and 'done'
1004 // include everything, so every step is completed.
1005 if (in_array($active, array('finished', 'done'))) {
1006   $active = NULL;
1007 }

```



```

1051     '#description' => st('Spaces are allowed; punctuation is not ...  

1052     allowed except for periods, hyphens, and underscores.'),  

1053     '#required' => TRUE,  

1054     '#weight' => -10,  

1055   );  

1056  

1056 $form['admin_account']['account']['mail'] = array('#type' => '...  

1057   textfield',  

1058   '#title' => st('E-mail address'),  

1059   '#maxlength' => EMAIL_MAX_LENGTH,  

1060   '#description' => st('All e-mails from the system will be sent to ...  

1061   this address. The e-mail address is not made public and will only ...  

1062   be used if you wish to receive a new password or wish to receive ...  

1063   certain news or notifications by e-mail.'),  

1064   '#required' => TRUE,  

1065   '#weight' => -5,  

1066 );  

1066 $form['admin_account']['account']['pass'] = array(  

1067   '#type' => 'password_confirm',  

1068   '#required' => TRUE,  

1069   '#size' => 25,  

1070   '#weight' => 0,  

1071 );  

1071  

1071 $form['server_settings'] = array(  

1072   '#type' => 'fieldset',  

1073   '#title' => st('Server settings'),  

1074   '#collapsible' => FALSE,  

1075 );  

1075 $form['server_settings']['date_default_timezone'] = array(  

1076   '#type' => 'select',  

1077   '#title' => st('Default time zone'),  

1078   '#default_value' => 0,  

1079   '#options' => _system_zonelist(),  

1080   '#description' => st('By default, dates in this site will be ...  

1081   displayed in the chosen time zone.'),  

1082   '#weight' => 5,  

1083 );  

1083  

1083 $form['server_settings']['clean_url'] = array(  

1084   '#type' => 'radios',  

1085   '#title' => st('Clean URLs'),  

1086   '#default_value' => 0,  

1087   '#options' => array(0 => st('Disabled'), 1 => st('Enabled')),  

1088   '#description' => st('This option makes Drupal emit "clean" URLs (...  

1089   i.e. without <code>?q=</code> in the URL).'),  

1090   '#disabled' => TRUE,  

1091   '#prefix' => '<div id="clean-url" class="install">',  

1092   '#suffix' => '</div>',  

1093   '#weight' => 10,  

1094 );  

1094  

1094 $form['server_settings']['update_status_module'] = array(  

1095   '#type' => 'checkboxes',  

1096 );

```

```

1101 '#title' => st('Update notifications'),
1102 '#options' => array(1 => st('Check for updates automatically')),
1103 '#default_value' => array(1),
1104 '#description' => st('With this option enabled, Drupal will notify...
1105 you when new releases are available. This will significantly ...
1106 enhance your site\'s security and is <strong>highly recommended</...
1107 strong>. This requires your site to periodically send anonymous ...
1108 information on its installed components to <a href="@drupal">...
1109 drupal.org</a>. For more information please see the <a href="...
1110 @update">update notification information</a>.'), array('@drupal' =>...
1111 'http://drupal.org', '@update' => 'http://drupal.org/handbook/...
1112 modules/update')) ,
1113 '#weight' => 15,
1114 ) ;

1115 $form['submit'] = array(
1116   '#type' => 'submit',
1117   '#value' => st('Save and continue'),
1118   '#weight' => 15,
1119 );
1120 $form['#action'] = $url;
1121 $form['#redirect'] = FALSE;

1122 // Allow the profile to alter this form. $form_state isn't available
1123 // here, but to conform to the hook_form_alter() signature, we pass
1124 // an empty array.
1125 $hook_form_alter = $_GET['profile'] . '_form_alter';
1126 if (function_exists($hook_form_alter)) {
1127   $hook_form_alter($form, array(), 'install_configure');
1128 }
1129 return $form;
1130 }

1131 /**
1132 * Form API validate for the site configuration form.
1133 */
1134 function install_configure_form_validate($form, &$amp;form_state) {
1135   if ($error = user_validate_name($form_state['values']['account'][...
1136     'name'])) {
1137     form_error($form['admin_account']['account']['name'], $error);
1138   }
1139   if ($error = user_validate_mail($form_state['values']['account'][...
1140     'mail'])) {
1141     form_error($form['admin_account']['account']['mail'], $error);
1142   }
1143   if ($error = user_validate_mail($form_state['values']['site_mail'])...
1144     [
1145       form_error($form['site_information']['site_mail'], $error);
1146     ]
1147   }
1148 }

1149 /**
1150 * Form API submit for the site configuration form.
1151 */

```

```

1141 | function install_configure_form_submit($form, &$form_state) {
1142 |   global $user;
1143 |
1144 |   variable_set('site_name', $form_state['values']['site_name']);
1145 |   variable_set('site_mail', $form_state['values']['site_mail']);
1146 |   variable_set('date_default_timezone', $form_state['values']...
1147 |     'date_default_timezone');
1148 |
1149 |   // Enable update.module if this option was selected.
1150 |   if ($form_state['values']['update_status_module'][1]) {
1151 |     drupal_install_modules(array('update'));
1152 |   }
1153 |
1154 |   // Turn this off temporarily so that we can pass a password through.
1155 |   variable_set('user_email_verification', FALSE);
1156 |   $form_state['old_values'] = $form_state['values'];
1157 |   $form_state['values'] = $form_state['values']['account'];
1158 |
1159 |   // We precreated user 1 with placeholder values. Let's save the real...
1160 |   // ... values.
1161 |   $account = user_load(1);
1162 |   $merge_data = array('init' => $form_state['values']['mail'],
1163 |     'roles'...
1164 |       => array(), 'status' => 1);
1165 |   user_save($account, array_merge($form_state['values'], $merge_data))...
1166 |   ;
1167 |
1168 |   // Log in the first user.
1169 |   user_authenticate($form_state['values']);
1170 |   $form_state['values'] = $form_state['old_values'];
1171 |   unset($form_state['old_values']);
1172 |   variable_set('user_email_verification', TRUE);
1173 |
1174 |   if (isset($form_state['values']['clean_url'])) {
1175 |     variable_set('clean_url', $form_state['values']['clean_url']);
1176 |   }
1177 |
1178 |   // The user is now logged in, but has no session ID yet, which
1179 |   // would be required later in the request, so remember it.
1180 |   $user->sid = session_id();
1181 |
1182 |   // Record when this install ran.
1183 |   variable_set('install_time', time());
1184 |
1185 |   // Start the installer.
1186 |   install_main();

```

1.4. Fichero update.php

```

<?php
// $Id: update.php,v 1.252.2.3 2009/03/30 11:15:11 goba Exp $

/*
 * @file
5

```

```

    * Administrative page for handling updates from one Drupal version to...
    *
    * Point your browser to "http://www.example.com/update.php" and ...
    * follow the
    * instructions.
10   *
    * If you are not logged in as administrator, you will need to modify ...
    * the access
    * check statement inside your settings.php file. After finishing the ...
    * upgrade,
    * be sure to open settings.php again, and change it back to its ...
    * original state!
    */
15 /**
    * Global flag to identify update.php run, and so avoid various ...
    * unwanted
    * operations, such as hook_init() and hook_exit() invokes, css/js ...
    * preprocessing
    * and translation, and solve some theming issues. This flag is ...
    * checked on several
20   * places in Drupal code (not just update.php).
    */
define( 'MAINTENANCE_MODE', 'update' );

/**
25   * Add a column to a database using syntax appropriate for PostgreSQL.
    * Save result of SQL commands in $ret array.
    *
    * Note: when you add a column with NOT NULL and you are not sure if ...
    * there are
    * already rows in the table, you MUST also add DEFAULT. Otherwise ...
    * PostgreSQL
30   * won't work when the table is not empty, and db_add_column() will ...
    * fail.
    * To have an empty string as the default, you must use: 'default' => ...
    * "''"
    * in the $attributes array. If NOT NULL and DEFAULT are set the ...
    * PostgreSQL
    * version will set values of the added column in old rows to the
    * DEFAULT value.
35   *
    * @param $ret
    *   Array to which results will be added.
    * @param $table
    *   Name of the table, without {}
40   * @param $column
    *   Name of the column
    * @param $type
    *   Type of column
    * @param $attributes
    *   Additional optional attributes. Recognized attributes:
45   *   not null => TRUE/FALSE

```

```

*      default  => NULL/FALSE/value (the value must be enclosed in '' ...
*      marks)
*  @return
*      nothing , but modifies $ret parameter.
50 */
function db_add_column(&$ret , $table , $column , $type , $attributes = ...
    array()) {
    if (array_key_exists( 'not null' , $attributes) and $attributes[ 'not ...
        null' ]) {
        $not_null = 'NOT NULL';
    }
    if (array_key_exists( 'default' , $attributes)) {
        if (is_null($attributes[ 'default' ])) {
            $default_val = 'NULL';
            $default = 'default NULL';
        }
        elseif ($attributes[ 'default' ] === FALSE) {
            $default = '';
        }
        else {
            $default_val = "$attributes[ default ]";
            $default = "default $attributes[ default ]";
        }
    }

    $ret [] = update_sql("ALTER TABLE {". $table ." } ADD $column $type");
    if (!empty($default)) {
        $ret [] = update_sql("ALTER TABLE {". $table ." } ALTER $column SET ...
            $default");
    }
    if (!empty($not_null)) {
        if (!empty($default)) {
            $ret [] = update_sql("UPDATE {". $table ." } SET $column = ...
                $default_val");
        }
        $ret [] = update_sql("ALTER TABLE {". $table ." } ALTER $column SET ...
            NOT NULL");
    }
}
80 /**
* Change a column definition using syntax appropriate for PostgreSQL.
* Save result of SQL commands in $ret array.
*
85 * Remember that changing a column definition involves adding a new ...
* column
* and dropping an old one. This means that any indices , primary keys ...
* and
* sequences from serial-type columns are dropped and might need to be
* recreated .
*
90 * @param $ret
*     Array to which results will be added.
* @param $table

```

```

*      Name of the table , without {}
* @param $column
*      Name of the column to change
* @param $column_new
*      New name for the column (set to the same as $column if you don't ...
*      want to change the name)
* @param $type
*      Type of column
* @param $attributes
*      Additional optional attributes . Recognized attributes :
*          not null => TRUE/FALSE
*          default  => NULL/FALSE/value (with or without '' , it won't be ...
*          added)
* @return
*      nothing , but modifies $ret parameter .
*/
function db_change_column(&$ret , $table , $column , $column_new , $type , ...
    $attributes = array()) {
    if (array_key_exists('not null' , $attributes) and $attributes['not ...
        null']) {
        $not_null = 'NOT NULL';
    }
    if (array_key_exists('default' , $attributes)) {
        if (is_null($attributes['default'])) {
            $default_val = 'NULL';
            $default = 'default NULL';
        }
        elseif ($attributes['default'] == FALSE) {
            $default = '';
        }
        else {
            $default_val = "$attributes[default]";
            $default = "default $attributes[default]";
        }
    }
    $ret [] = update_sql("ALTER TABLE ".$table.") RENAME $column TO ...
        $column ."_old");
    $ret [] = update_sql("ALTER TABLE ".$table.") ADD $column_new ...
        $type");
    $ret [] = update_sql("UPDATE ".$table.") SET $column_new = ".$...
        $column ."_old");
    if (!$default) { $ret [] = update_sql("ALTER TABLE ".$table.") ...
        ALTER $column_new SET $default"); }
    if ($not_null) { $ret [] = update_sql("ALTER TABLE ".$table.") ...
        ALTER $column_new SET NOT NULL"); }
    $ret [] = update_sql("ALTER TABLE ".$table.") DROP ".$...
        $column ."_old");
}

/**
 * Perform one update and store the results which will later be ...
 * displayed on
 * the finished page .

```

```

*
* An update function can force the current and all later updates for ...
* this
* module to abort by returning a $ret array with an element like:
* $ret['#abort'] = array('success' => FALSE, 'query' => 'What went ...
* wrong');
140 * The schema version will not be updated in this case, and all the
* aborted updates will continue to appear on update.php as updates ...
* that
* have not yet been run.
*
* @param $module
145 * The module whose update will be run.
* @param $number
* The update number to run.
* @param $context
* The batch context array
150 */
function update_do_one($module, $number, &$context) {
    // If updates for this module have been aborted
    // in a previous step, go no further.
    if (!empty($context['results'][$module]['#abort'])) {
155        return;
    }

    $function = $module . '_update_' . $number;
    if (function_exists($function)) {
160        $ret = $function($context['sandbox']);
    }

    if (isset($ret['#finished'])) {
        $context['finished'] = $ret['#finished'];
        unset($ret['#finished']);
    }

    if (!isset($context['results'][$module])) {
165        $context['results'][$module] = array();
    }
    if (!isset($context['results'][$module][$number])) {
        $context['results'][$module][$number] = array();
    }
    $context['results'][$module][$number] = array_merge($context['...
170        results'][$module][$number], $ret);

    if (!empty($ret['#abort'])) {
        $context['results'][$module]['#abort'] = TRUE;
    }
    // Record the schema update if it was completed successfully.
175    if ($context['finished'] == 1 && empty($context['results'][$module][...
        '#abort'])) {
        drupal_set_installed_schema_version($module, $number);
    }

    $context['message'] = 'Updating ' . check_plain($module) . ' module';

```

```

185    }

function update_selection_page() {
  $output = '<p>The version of Drupal you are updating from has been ...
  automatically detected. You can select a different version, but ...
  you should not need to.</p>';
  $output .= '<p>Click Update to start the update process.</p>';

190  drupal_set_title('Drupal database update');
  $output .= drupal_get_form('update_script_selection_form');

  update_task_list('select');

195  return $output;
}

function update_script_selection_form() {
  $form = array();
  $form['start'] = array(
    '#tree' => TRUE,
    '#type' => 'fieldset',
    '#title' => 'Select versions',
    '#collapsible' => TRUE,
    '#collapsed' => TRUE
  );

  // Ensure system.module's updates appear first
200  $form['start']['system'] = array();

  $modules = drupal_get_installed_schema_version(NULL, FALSE, TRUE);
  foreach ($modules as $module => $schema_version) {
    $updates = drupal_get_schema_versions($module);
    // Skip incompatible module updates completely, otherwise test ...
    // schema versions.
    if (!update_check_incompatibility($module) && $updates !== FALSE ...
&& $schema_version >= 0) {
      // module_invoke returns NULL for nonexisting hooks, so if no ...
      // updates
      // are removed, it will == 0.
      $last_removed = module_invoke($module, 'update_last_removed');
210  if ($schema_version < $last_removed) {
        $form['start'][$module] = array(
          '#value' => '<em>' . $module . '</em> module can not be ...
updated. Its schema version is ' . $schema_version . '. Updates up ...
to and including ' . $last_removed . ' have been removed in this ...
release. In order to update <em>' . $module . '</em> module, you ...
will first <a href="http://drupal.org/upgrade">need to upgrade</a>...
to the last version in which these updates were available.' ,
          '#prefix' => '<div class="warning">',
          '#suffix' => '</div>',
        );
        $form['start'][ '#collapsed' ] = FALSE;
        continue;
      }
    }
}

```

```

230     $updates = drupal_map_assoc($updates);
231     $updates[] = 'No updates available';
232     $default = $schema_version;
233     foreach (array_keys($updates) as $update) {
234       if ($update > $schema_version) {
235         $default = $update;
236         break;
237       }
238     }
239     $form['start'][$module] = array(
240       '#type' => 'select',
241       '#title' => $module . ' module',
242       '#default_value' => $default,
243       '#options' => $updates,
244     );
245   }
246 }

247 $form['has_js'] = array(
248   '#type' => 'hidden',
249   '#default_value' => FALSE,
250 );
251 $form['submit'] = array(
252   '#type' => 'submit',
253   '#value' => 'Update',
254 );
255 return $form;
}

256 function update_batch() {
257   global $base_url;
258
259   $operations = array();
260   // Set the installed version so updates start at the correct place.
261   foreach ($_POST['start'] as $module => $version) {
262     drupal_set_installed_schema_version($module, $version - 1);
263     $updates = drupal_get_schema_versions($module);
264     $max_version = max($updates);
265     if ($version <= $max_version) {
266       foreach ($updates as $update) {
267         if ($update >= $version) {
268           $operations[] = array('update_do_one', array($module, ...
269             $update));
270         }
271       }
272     }
273   }
274
275   $batch = array(
276     'operations' => $operations,
277     'title' => 'Updating',
278     'init_message' => 'Starting updates',
279     'error_message' => 'An unrecoverable error has occurred. You can ...
280     find the error message below. It is advised to copy it to the ...
281     clipboard for reference.',
282   );

```

```

280     'finished' => 'update_finished',
281 );
batch_set($batch);
batch_process($base_url . '/update.php?op=results', $base_url . '/...
    update.php');
}
285 function update_finished($success, $results, $operations) {
    // clear the caches in case the data has been updated.
    drupal_flush_all_caches();

290 $_SESSION['update_results'] = $results;
$_SESSION['update_success'] = $success;
$_SESSION['updates_remaining'] = $operations;
}

295 function update_results_page() {
    drupal_set_title('Drupal database update');
    // NOTE: we can't use l() here because the URL would point to '...
        update.php?q=admin'.
$links[] = '<a href="'. base_path() .'">Main page</a>';
$links[] = '<a href="'. base_path() . '?q=admin">Administration pages...
    </a>';
}
300 update_task_list();
// Report end result
305 if (module_exists('dblog')) {
    $log_message = ' All errors have been <a href="'. base_path() . '?q...
        =admin/reports/dblog">logged</a>. ';
}
else {
    $log_message = ' All errors have been logged. ';
}

310 if ($_SESSION['update_success']) {
    $output = '<p>Updates were attempted. If you see no failures below...
        , you may proceed happily to the <a href="'. base_path() . '?q=...
            admin">administration pages</a>. Otherwise, you may need to update...
        your database manually.</p>';
}
else {
    list($module, $version) = array_pop(reset($_SESSION['...
        updates_remaining']));
    $output = '<p class="error">The update process was aborted ...
        prematurely while running <strong>update #' . $version . ' in ' . ...
        $module . '.module</strong>.' . $log_message;
    if (module_exists('dblog')) {
        $output .= ' You may need to check the <code>watchdog</code> ...
            database table manually.';
    }
    $output .= '</p>';
}
320 if (!empty($GLOBALS['update_free_access'])) {

```

```

$output .= "<p><strong>Reminder: don't forget to set the <code>\...
$update_free_access</code> value in your <code>settings.php</code>...
file back to <code>FALSE</code>. </strong></p>";
}

325 $output .= theme('item_list', $links);

// Output a list of queries executed
if (!empty($_SESSION['update_results'])) {
    $output .= '<div id="update-results">';
    $output .= '<h2>The following queries were executed</h2>';
    foreach ($_SESSION['update_results'] as $module => $updates) {
        $output .= '<h3>' . $module . ' module</h3>';
        foreach ($updates as $number => $queries) {
            if ($number != '#abort') {
                $output .= '<h4>Update #' . $number . '</h4>';
                $output .= '<ul>';
                foreach ($queries as $query) {
                    if ($query['success']) {
                        $output .= '<li class="success">' . $query['query'] . '<...';
                        li>';
                    }
                    else {
                        $output .= '<li class="failure"><strong>Failed:</strong>...';
                        . $query['query'] . '</li>';
                    }
                }
                if (!count($queries)) {
                    $output .= '<li class="none">No queries</li>';
                }
            }
            $output .= '</ul>';
        }
    }
    $output .= '</div>';
}
unset($_SESSION['update_results']);
unset($_SESSION['update_success']);

return $output;
}

360 function update_info_page() {
    // Change query-strings on css/js files to enforce reload for all ...
    // users.
    drupal_flush_css_js();
    // Flush the cache of all data for the update status module.
365 if (db_table_exists('cache_update')) {
    cache_clear_all('*', 'cache_update', TRUE);
}

update_task_list('info');
drupal_set_title('Drupal database update');
$token = drupal_get_token('update');

```

```

$output = '<p>Use this utility to update your database whenever a ...
new release of Drupal or a module is installed.</p><p>For more ...
detailed information, see the <a href="http://drupal.org/node...
/258">Installation and upgrading handbook</a>. If you are unsure ...
what these terms mean you should probably contact your hosting ...
provider.</p>';
$output .= "<ol>\n";
$output .= "<li><strong>Back up your database</strong>. This process...
will change your database values and in case of emergency you may...
need to revert to a backup.</li>\n";
375 $output .= "<li><strong>Back up your code</strong>. Hint: when ...
backing up module code, do not leave that backup in the 'modules' ...
or 'sites/*/modules' directories as this may confuse Drupal's auto...
-discovery mechanism.</li>\n";
$output .= '<li>Put your site into <a href="'. base_path() . '?q=...
admin/settings/site-maintenance">maintenance mode</a>.</li>' . "\n";
$output .= "<li>Install your new files in the appropriate location, ...
as described in the handbook.</li>\n";
$output .= "</ol>\n";
$output .= "<p>When you have performed the steps above, you may ...
proceed.</p>\n";
380 $output .= '<form method="post" action="update.php?op=selection&...
token=' . $token . '"><p><input type="submit" value="Continue" /></p...
></form>';
$output .= "\n";
return $output;
}

385 function update_access_denied_page() {
  drupal_set_title('Access denied');
  return '<p>Access denied. You are not authorized to access this page...
. Please log in as the admin user (the first user you created). If...
you cannot log in, you will have to edit <code>settings.php</code...
> to bypass this access check. To do this:</p>
<ol>
  <li>With a text editor find the settings.php file on your system. ...
    From the main Drupal directory that you installed all the files ...
    into, go to <code>sites/your_site_name</code> if such directory ...
    exists, or else to <code>sites/default</code> which applies ...
    otherwise.</li>
390  <li>There is a line inside your settings.php file that says <code>...
    $update_free_access = FALSE;</code>. Change it to <code>...
    $update_free_access = TRUE;</code>.</li>
  <li>As soon as the update.php script is done, you must change the ...
    settings.php file back to its original form with <code>...
    $update_free_access = FALSE;</code>.</li>
  <li>To avoid having this problem in future, remember to log in to ...
    your website as the admin user (the user you first created) before...
    you backup your database at the beginning of the update process...
    .</li>
</ol>';
}
395 /**

```

```

    * Create the batch table.
    *
    * This is part of the Drupal 5.x to 6.x migration.
400   */
function update_create_batch_table() {

    // If batch table exists, update is not necessary
    if (db_table_exists('batch')) {
        return;
    }

    $schema['batch'] = array(
        'fields' => array(
            'bid' => array('type' => 'serial', 'unsigned' => TRUE, '...
not null' => TRUE),
            'token' => array('type' => 'varchar', 'length' => 64, 'not ...
null' => TRUE),
            'timestamp' => array('type' => 'int', 'not null' => TRUE),
            'batch' => array('type' => 'text', 'not null' => FALSE, '...
size' => 'big')
        ),
        'primary key' => array('bid'),
        'indexes' => array('token' => array('token'))
    );
}

$ret = array();
420 db_create_table($ret, 'batch', $schema['batch']);
return $ret;
}

/**
425 * Disable anything in the {system} table that is not compatible with ...
the
* current version of Drupal core.
*/
function update_fix_compatibility() {
    $ret = array();
    $incompatible = array();
    $query = db_query("SELECT name, type, status FROM {system} WHERE ...
status = 1 AND type IN ('module', 'theme')");
    while ($result = db_fetch_object($query)) {
        if (update_check_incompatibility($result->name, $result->type)) {
            $incompatible[] = $result->name;
435        }
    }
    if (!empty($incompatible)) {
        $ret[] = update_sql("UPDATE {system} SET status = 0 WHERE name IN ...
('" . implode("','", $incompatible) . "')");
    }
    return $ret;
}

/**
440 * Helper function to test compatibility of a module or theme.
*/

```

```

445  /*
446   * Function update_check_incompatibility($name, $type = 'module') {
447   *   static $themes, $modules;
448   *
449   *   // Store values of expensive functions for future use.
450   *   if (empty($themes) || empty($modules)) {
451   *     $themes = _system_theme_data();
452   *     $modules = module_rebuild_cache();
453   *   }
454   *
455   *   if ($type == 'module' && isset($modules[$name])) {
456   *     $file = $modules[$name];
457   *   }
458   *   else if ($type == 'theme' && isset($themes[$name])) {
459   *     $file = $themes[$name];
460   *   }
461   *   if (!isset($file)
462   *       || !isset($file->info['core'])
463   *       || $file->info['core'] != DRUPAL_CORE_COMPATIBILITY
464   *       || version_compare/phpversion(), $file->info['php']) < 0) {
465   *     return TRUE;
466   *   }
467   *   return FALSE;
468   */
469
470 /**
471 * Perform Drupal 5.x to 6.x updates that are required for update.php
472 * to function properly.
473 *
474 * This function runs when update.php is run the first time for 6.x,
475 * even before updates are selected or performed. It is important
476 * that if updates are not ultimately performed that no changes are
477 * made which make it impossible to continue using the prior version.
478 * Just adding columns is safe. However, renaming the
479 * system.description column to owner is not. Therefore, we add the
480 * system.owner column and leave it to system_update_6008() to copy
481 * the data from description and remove description. The same for
482 * renaming locales_target.locale to locales_target.language, which
483 * will be finished by locale_update_6002().
484 */
485 function update_fix_d6_requirements() {
486   $ret = array();
487
488   if (drupal_get_installed_schema_version('system') < 6000 && !...
489       variable_get('update_d6_requirements', FALSE)) {
490     $spec = array('type' => 'int', 'size' => 'small', 'default' => 0, ...
491       'not null' => TRUE);
492     db_add_field($ret, 'cache', 'serialized', $spec);
493     db_add_field($ret, 'cache_filter', 'serialized', $spec);
494     db_add_field($ret, 'cache_page', 'serialized', $spec);
495     db_add_field($ret, 'cache_menu', 'serialized', $spec);
496
497     db_add_field($ret, 'system', 'info', array('type' => 'text'));

```

```

    db_add_field($ret, 'system', 'owner', array('type' => 'varchar', ...
length' => 255, 'not null' => TRUE, 'default' => ''));

    if (db_table_exists('locales_target')) {
      db_add_field($ret, 'locales_target', 'language', array('type' =>...
'varchar', 'length' => 12, 'not null' => TRUE, 'default' => ''));

    }
    if (db_table_exists('locales_source')) {
      db_add_field($ret, 'locales_source', 'textgroup', array('type' ...
=> 'varchar', 'length' => 255, 'not null' => TRUE, 'default' => ...
'default'));
      db_add_field($ret, 'locales_source', 'version', array('type' => ...
'varchar', 'length' => 20, 'not null' => TRUE, 'default' => 'none'));
    }
  variable_set('update_d6_requirements', TRUE);

// Create the cache_block table. See system_update_6027() for more...
details.

$schema['cache_block'] = array(
  'fields' => array(
    'cid' => array('type' => 'varchar', 'length' => 255, '...
not null' => TRUE, 'default' => ''),
    'data' => array('type' => 'blob', 'not null' => FALSE, '...
size' => 'big'),
    'expire' => array('type' => 'int', 'not null' => TRUE, '...
default' => 0),
    'created' => array('type' => 'int', 'not null' => TRUE, '...
default' => 0),
    'headers' => array('type' => 'text', 'not null' => FALSE),
    'serialized' => array('type' => 'int', 'size' => 'small', 'not...
null' => TRUE, 'default' => 0)
  ),
  'indexes' => array('expire' => array('expire')),
  'primary key' => array('cid'),
);
db_create_table($ret, 'cache_block', $schema['cache_block']);

return $ret;
}

/**
 * Add the update task list to the current page.
 */
function update_task_list($active = NULL) {
  // Default list of tasks.
  $tasks = array(
    'info' => 'Overview',
    'select' => 'Select updates',
    'run' => 'Run updates',
    'finished' => 'Review log',
  );
  drupal_set_content('left', theme('task_list', $tasks, $active));
}

```

```

    }

540 /**
 * Check update requirements and report any errors.
 */
function update_check_requirements() {
  // Check the system module requirements only.
  $requirements = module_invoke('system', 'requirements', 'update');
  $severity = drupal_requirements_severity($requirements);

  // If there are issues, report them.
  if ($severity != REQUIREMENT_OK) {
550   foreach ($requirements as $requirement) {
     if (isset($requirement['severity']) && $requirement['severity'] ...
       != REQUIREMENT_OK) {
       $message = isset($requirement['description']) ? $requirement['...
         description'] : '';
       if (isset($requirement['value']) && $requirement['value']) {
         $message .= '(Currently using ' . $requirement['title'] . ' ...
           . $requirement['value'] . ')';
       }
       drupal_set_message($message, 'warning');
     }
   }
560 }

// Some unavoidable errors happen because the database is not yet up-...
// to-date.
// Our custom error handler is not yet installed, so we just suppress ...
// them.
ini_set('display_errors', FALSE);
565 require_once './includes/bootstrap.inc';

// We only load DRUPAL_BOOTSTRAP_CONFIGURATION for the update ...
// requirements
// check to avoid reaching the PHP memory limit.
570 $op = isset($_REQUEST['op']) ? $_REQUEST['op'] : '';
if (empty($op)) {
  // Minimum load of components.
  drupal_bootstrap(DRUPAL_BOOTSTRAP_CONFIGURATION);

575 require_once './includes/install.inc';
require_once './includes/file.inc';
require_once './modules/system/system.install';

  // Load module basics.
580 include_once './includes/module.inc';
$module_list['system']['filename'] = 'modules/system/system.module';
$module_list['filter']['filename'] = 'modules/filter/filter.module';
module_list(TRUE, FALSE, FALSE, $module_list);
drupal_load('module', 'system');
drupal_load('module', 'filter');

```

```

// Set up $language, since the installer components require it.
drupal_init_language();

590 // Set up theme system for the maintenance page.
drupal_maintenance_theme();

// Check the update requirements for Drupal.
update_check_requirements();

595 // Display the warning messages (if any) in a dedicated maintenance ...
// page,
// or redirect to the update information page if no message.
$messages = drupal_set_message();
if (!empty($messages['warning'])) {
600   drupal_maintenance_theme();
   print theme('update_page', '<form method="post" action="update.php...
?op=info"><input type="submit" value="Continue" /></form>', FALSE);
   ;
   exit;
}
install_goto('update.php?op=info');

605 }

drupal_bootstrap(DRUPAL_BOOTSTRAP_FULL);
drupal_maintenance_theme();

610 // This must happen *after* drupal_bootstrap(), since it calls
// variable_(get/set), which only works after a full bootstrap.
update_create_batch_table();

// Turn error reporting back on. From now on, only fatal errors (which...
// are
615 // not passed through the error handler) will cause a message to be ...
// printed.
ini_set('display_errors', TRUE);

// Access check:
if (!empty($update_free_access) || $user->uid == 1) {
620
  include_once './includes/install.inc';
  include_once './includes/batch.inc';
  drupal_load_updates();

  update_fix_d6_requirements();
  update_fix_compatibility();

  $op = isset($_REQUEST['op']) ? $_REQUEST['op'] : '';
  switch ($op) {
630    case 'selection':
      if (isset($_GET['token']) && $_GET['token'] == drupal_get_token(
        'update')) {
        $output = update_selection_page();
        break;
  }
}

```

```

        }

635    case 'Update':
636      if (isset($_GET['token']) && $_GET['token'] == drupal_get_token('update')) {
637        update_batch();
638        break;
639      }

640      // update.php ops
641      case 'info':
642        $output = update_info_page();
643        break;

644      case 'results':
645        $output = update_results_page();
646        break;

647      // Regular batch ops : defer to batch processing API
648      default:
649        update_task_list('run');
650        $output = _batch_page();
651        break;
652      }
653    }
654    else {
655      $output = update_access_denied_page();
656    }
657  if (isset($output) && $output) {
658    // We defer the display of messages until all updates are done.
659    $progress_page = ($batch = batch_get()) && isset($batch['running']);
660    print theme('update_page', $output, !$progress_page);
661  }
662}

```

1.5. Fichero xmlrpc.php

```

<?php
// $Id: xmlrpc.php, v 1.15 2005/12/10 19:26:47 dries Exp $

5 /**
 * @file
 * PHP page for handling incoming XML-RPC requests from clients.
 */

include_once './includes/bootstrap.inc';
10 drupal_bootstrap(DRUPAL_BOOTSTRAP_FULL);
include_once './includes/xmlrpc.inc';
include_once './includes/xmlrpcs.inc';

xmlrpc_server(module_invoke_all('xmlrpc'));

```

Capítulo 2

Carpeta drupal/modules/aggregator

2.1. Fichero aggregator-feed-source.tpl.php

```
1 <?php
// $Id: aggregator-feed-source.tpl.php, v 1.1 2007/09/13 08:02:38 goba ...
Exp $

/*
 * @file aggregator-feed-source.tpl.php
6 * Default theme implementation to present the source of the feed.
 *
 * The contents are render above feed listings when browsing source ...
 * feeds.
 * For example, "example.com/aggregator/sources/1".
 *
11 * Available variables:
 * - $source_icon: Feed icon linked to the source. Rendered through
 *   theme_feed_icon().
 * - $source_image: Image set by the feed source.
 * - $source_description: Description set by the feed source.
16 * - $source_url: URL to the feed source.
 * - $last_checked: How long ago the feed was checked locally.
 *
 * @see template_preprocess()
 * @see template_preprocess_aggregator_feed_source()
21 */
?>
<div class="feed-source">
<?php print $source_icon; ?>
<?php print $source_image; ?>
26 <div class="feed-description">
    <?php print $source_description; ?>
</div>
<div class="feed-url">
    <em><?php print t('URL:'); ?></em> <a href="<?php print ...
        $source_url; ?>"><?php print $source_url; ?></a>
31 </div>
```

```

<div class="feed-updated">
  <em><?php print t('Updated: ') ; ?></em> <?php print $last_checked; ...
  ?>
</div>
</div>

```

2.2. Fichero aggregator-item.tpl.php

```

<?php
// $Id: aggregator-item.tpl.php, v 1.1 2007/09/13 08:02:38 goba Exp $

/*
 * @file aggregator-item.tpl.php
 * Default theme implementation to format an individual feed item for ...
 * display
 * on the aggregator page.
 *
 * Available variables:
 * - $feed_url: URL to the originating feed item.
 * - $feed_title: Title of the feed item.
 * - $source_url: Link to the local source section.
 * - $source_title: Title of the remote source.
 * - $source_date: Date the feed was posted on the remote source.
 * - $content: Feed item content.
 * - $categories: Linked categories assigned to the feed.
 *
 * @see template_preprocess()
 * @see template_preprocess_aggregator_item()
 */
?>
<div class="feed-item">
  <h3 class="feed-item-title">
    <a href="<?php print $feed_url; ?>"><?php print $feed_title; ?></a...
    >
  </h3>

  <div class="feed-item-meta">
    <?php if ($source_url) : ?>
      <a href="<?php print $source_url; ?>" class="feed-item-source"><?...
        <?php print $source_title; ?></a> -
    <?php endif; ?>
      <span class="feed-item-date"><?php print $source_date; ?></span>
    </div>

    <?php if ($content) : ?>
      <div class="feed-item-body">
        <?php print $content; ?>
      </div>
    <?php endif; ?>

    <?php if ($categories) : ?>
      <div class="feed-item-categories">

```

2.3. FICHERO AGGREGATOR-SUMMARY-ITEMS.TPL.PHP 46

```
1  <?php print t( 'Categories' ); ?>: <?php print implode( ' ', ...  
2   $categories); ?>  
3   </div>  
45  <?php endif ;?>  
46  </div>
```

2.3. Fichero aggregator-summary-items.tpl.php

```
1  <?php  
2   // $Id: aggregator-summary-items.tpl.php , v 1.1 2007/09/13 08:02:38 ...  
3   gobal Exp $  
4  
4  /**  
5   * @file aggregator-summary-items.tpl.php  
6   * Default theme implementation to present feeds as list items.  
7   *  
8   * Each iteration generates a single feed source or category.  
9   *  
10  * Available variables:  
11  * - $title: Title of the feed or category.  
12  * - $summary_list: Unordered list of linked feed items generated ...  
13  *   through  
14  *   theme_item_list().  
15  * - $source_url: URL to the local source or category.  
16  *  
17  * @see template_preprocess()  
18  * @see template_preprocess_aggregator_summary-items()  
19  */  
19 ?>  
20  <h2><?php print $title; ?></h2>  
21  <?php print $summary_list; ?>  
22  <div class="links">  
23  <a href=<?php print $source_url; ?>"><?php print t('More'); ?></a>  
24  </div>
```

2.4. Fichero aggregator-summary-item.tpl.php

```
1  <?php  
2   // $Id: aggregator-summary-item.tpl.php , v 1.1 2007/09/13 08:02:38 ... gobal...  
3   gobal Exp $  
4  
4  /**  
5   * @file aggregator-summary-item.tpl.php  
6   * Default theme implementation to present a linked feed item for ...  
7   * summaries.  
8   *  
9   * Available variables:  
10  * - $feed_url: Link to originating feed.
```

```

11  * - $feed_title: Title of feed.
12  * - $feed_age: Age of remote feed.
13  * - $source_url: Link to remote source.
14  * - $source_title: Locally set title for the source.
15  *
16  * @see template preprocess()
17  * @see template preprocess_aggregator_summary_item()
18  */
?>
<a href=<?php print $feed_url; ?>><?php print $feed_title; ?></a> <...
    span class="age"><?php print $feed_age; ?></span><?php if (...$source_url) : ?>, <span class="source"><a href=<?php print ...
        $source_url; ?>><?php print $source_title; ?></a></span><?php ...
            endif; ?>

```

2.5. Fichero aggregator-wrapper.tpl.php

```

1  <?php
// $Id: aggregator-wrapper.tpl.php , v 1.1 2007/09/13 08:02:38 goba Exp ...
§

/**
 * @file comment-wrapper.tpl.php
6  * Default theme implementation to wrap aggregator content.
*
* Available variables:
* - $content: All aggregator content.
* - $page: Pager links rendered through theme_pager().
11 *
* @see template preprocess()
* @see template preprocess_comment_wrapper()
*/
?>
16 <div id="aggregator">
    <?php print $content; ?>
    <?php print $pager; ?>
</div>

```

Capítulo 3

Carpeta drupal/modules/block

3.1. Fichero block-admin-display-form.tpl.php

```
1 <?php
// $Id: block-admin-display-form.tpl.php, v 1.3 2008/01/16 22:57:26 ...
goba Exp $

6 /**
 * @file block-admin-display-form.tpl.php
 * Default theme implementation to configure blocks.
 *
 * Available variables:
 * - $block_regions: An array of regions. Keyed by name with the title...
 *   as value.
 * - $block_listing: An array of blocks keyed by region and then delta...
 *
11 * - $form_submit: Form submit button.
 * - $throttle: TRUE or FALSE depending on throttle module being ...
 *   enabled.
 *
 * Each $block_listing[$region] contains an array of blocks for that ...
 * region.
 *
16 * Each $data in $block_listing[$region] contains:
 * - $data->region_title: Region title for the listed block.
 * - $data->block_title: Block title.
 * - $data->region_select: Drop-down menu for assigning a region.
 * - $data->weight_select: Drop-down menu for setting weights.
21 * - $data->throttle_check: Checkbox to enable throttling.
 * - $data->configure_link: Block configuration link.
 * - $data->delete_link: For deleting user added blocks.
 *
 * @see template_preprocess_block_admin_display()
26 * @see theme_block_admin_display()
 */
?>
<?php
// Add table javascript.
drupal_add_js('misc/tableheader.js');
drupal_add_js(drupal_get_path('module', 'block') . '/block.js');
```

3.1. FICHERO BLOCK-ADMIN-DISPLAY-FORM.TPL.PHP 49

```

foreach ($block_regions as $region => $title) {
  drupal_add_tabledrag('blocks', 'match', 'sibling', 'block-region-...
  select', 'block-region-' . $region, NULL, FALSE);
  drupal_add_tabledrag('blocks', 'order', 'sibling', 'block-weight', ...
  'block-weight-' . $region);
36  }
?>
<table id="blocks" class="sticky-enabled">
  <thead>
    <tr>
      <th><?php print t('Block'); ?></th>
      <th><?php print t('Region'); ?></th>
      <th><?php print t('Weight'); ?></th>
      <?php if ($throttle): ?>
        <th><?php print t('Throttle'); ?></th>
46  <?php endif; ?>
      <th colspan="2"><?php print t('Operations'); ?></th>
    </tr>
  </thead>
  <tbody>
    <?php $row = 0; ?>
    <?php foreach ($block_regions as $region => $title): ?>
      <tr class="region region-<?php print $region?>">
        <td colspan="<?php print $throttle ? '6' : '5'; ?>" class="...
region"><?php print $title; ?></td>
        </tr>
        <tr class="region-message region-<?php print $region?>-message ...
<?php print empty($block_listing[$region]) ? 'region-empty' : '...
region-populated'; ?>">
          <td colspan="<?php print $throttle ? '6' : '5'; ?>"><em><?php ...
print t('No blocks in this region'); ?></em></td>
          </tr>
          <?php foreach ($block_listing[$region] as $delta => $data): ?>
            <tr class="draggable <?php print $row % 2 == 0 ? 'odd' : 'even';...
?><?php print $data->row_class ? '' . $data->row_class : ''; ?>">
              <td class="block"><?php print $data->block_title; ?></td>
              <td><?php print $data->region_select; ?></td>
              <td><?php print $data->weight_select; ?></td>
              <?php if ($throttle): ?>
                <td><?php print $data->throttle_check; ?></td>
66  <?php endif; ?>
                <td><?php print $data->configure_link; ?></td>
                <td><?php print $data->delete_link; ?></td>
              </tr>
              <?php $row++; ?>
71  <?php endforeach; ?>
            <?php endforeach; ?>
          </tbody>
        </table>
76 <?php print $form_submit; ?>

```

Capítulo 4

Carpeta drupal/modules/book

4.1. Fichero book-all-books-block.tpl.php

```
<?php
// $Id: book-all-books-block.tpl.php, v 1.1 2007/11/04 14:29:09 gobal ...
Exp $
```

4 /**
 * @file book-all-books-block.tpl.php
 * Default theme implementation for rendering book outlines within a ...
 * block.
 * This template is used only when the block is configured to "show ...
 * block on
 * all pages" which presents Multiple independent books on all pages.
9 *
 * Available variables:
 * - \$book_menus: Array of book outlines rendered as an unordered list...
 * . It is
 * keyed to the parent book ID which is also the ID of the parent ...
 * node
 * containing an entire outline.
14 *
 * @see template_preprocess_book_all_books_block()
 */
?>
<?php foreach (\$book_menus as \$book_id => \$menu) : ?>
19 <div id="book-block-menu-<?php print \$book_id; ?>" class="book-block-...
 menu">
 <?php print \$menu; ?>
</div>
<?php endforeach; ?>

4.2. Fichero book-export-html.tpl.php

```
<?php
// $Id: book-export-html.tpl.php, v 1.1.2.1 2009/05/13 19:11:04 gobal ...
Exp $
```

3

```


    /**
     * @file book-export-html.tpl.php
     * Default theme implementation for printed version of book outline.
     *
8    * Available variables:
     * - $title: Top level node title.
     * - $head: Header tags.
     * - $language: Language code, e.g. "en" for english.
     * - $language_rtl: TRUE or FALSE depending on right to left language ...
     *   scripts.
13   * - $base_url: URL to home page.
     * - $content: Nodes within the current outline rendered through
     *   book-node-export-html.tpl.php.
     *
     * @see template_preprocess_book_export_html()
18   */
?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http...
     ://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" lang="php print $language...
     -&gt;language; ?&gt;" xml:lang="<?php print $language-&gt;language; ?&gt;"&gt;
&lt;head&gt;
23   &lt;?php print $head; ?&gt;
   &lt;title&gt;&lt;?php print $title; ?&gt;&lt;/title&gt;
   &lt;base href="<?php print $base_url; ?&gt;" /&gt;
   &lt;link type="text/css" rel="stylesheet" href="misc/print.css" /&gt;
   &lt;?php if ($language_rtl): ?&gt;
28     &lt;link type="text/css" rel="stylesheet" href="misc/print-rtl.css"...
     /&gt;
     &lt;?php endif; ?&gt;
&lt;/head&gt;
&lt;body&gt;
&lt;?php
33   /**
     * The given node is /embedded to its absolute depth in a top ...
     * level
     * section/. For example, a child node with depth 2 in the ...
     * hierarchy is
     * contained in (otherwise empty) &amp;lt;div&amp;gt; elements ...
     * corresponding to
     * depth 0 and depth 1. This is intended to support WYSIWYG output...
     - e.g.,
     * level 3 sections always look like level 3 sections, no matter ...
     * their
     * depth relative to the node selected to be exported as printer-...
     friendly
     * HTML.
     */
$div_close = '';
43   ?&gt;
   &lt;?php for ($i = 1; $i &lt; $depth; $i++) : ?&gt;
     &lt;div class="section-&lt;?php print $i; ?&gt;"&gt;
       &lt;?php $div_close .= '&lt;/div&gt;'; ?&gt;
   &lt;?php endfor; ?&gt;
</code

```

```

48    <?php print $contents; ?>
49    <?php print $div_close; ?>
50
51    </body>
52 </html>

```

4.3. Fichero book-navigation.tpl.php

```

<?php
// $Id: book-navigation.tpl.php, v 1.1 2007/11/04 14:29:09 goba Exp $

/*
 * @file book-navigation.tpl.php
 * Default theme implementation to navigate books. Presented under ...
 * nodes that
 * are a part of book outlines.
 *
 * Available variables:
 * - $tree: The immediate children of the current node rendered as an
 * unordered list.
 * - $current_depth: Depth of the current node within the book outline...
 *
 * Provided for context.
 * - $prev_url: URL to the previous node.
 * - $prev_title: Title of the previous node.
 * - $parent_url: URL to the parent node.
 * - $parent_title: Title of the parent node. Not printed by default. ...
 * Provided
 * as an option.
 * - $next_url: URL to the next node.
 * - $next_title: Title of the next node.
 * - $has_links: Flags TRUE whenever the previous, parent or next data...
 * has a
 * value.
 * - $book_id: The book ID of the current outline being viewed. Same ...
 * as the
 * node ID containing the entire outline. Provided for context.
 * - $book_url: The book/node URL of the current outline being viewed.
 * Provided as an option. Not used by default.
 * - $book_title: The book/node title of the current outline being ...
 * viewed.
 * Provided as an option. Not used by default.
 *
 * @see template_preprocess_book_navigation()
 */
?>
<?php if ($tree || $has_links): ?>
<div id="book-navigation-<?php print $book_id; ?>" class="book-...
navigation">
<?php print $tree; ?>

```

```

37  <?php if ($has_links) : ?>
<div class="page-links clear-block">
    <?php if ($prev_url) : ?>
        <a href="php print $prev_url; ?&gt;" class="page-previous" ...
            title="<?php print t('Go to previous page'); ?&gt;"><?php print t('...
                ') . $prev_title; ?></a>
    <?php endif; ?>
    <?php if ($parent_url) : ?>
        <a href="php print $parent_url; ?&gt;" class="page-up" title="...
            &lt;?php print t('Go to parent page'); ?&gt;"><?php print t('up'); ?></a...
        >
    <?php endif; ?>
    <?php if ($next_url) : ?>
        <a href="php print $next_url; ?&gt;" class="page-next" title="...
            &lt;?php print t('Go to next page'); ?&gt;"><?php print $next_title . t('...
                ') ; ?></a>
    <?php endif; ?>
</div>
<?php endif; ?>

</div>
52 <?php endif; ?>

```

4.4. Fichero book-node-export-html.tpl.php

```

<?php
// $Id: book-node-export-html.tpl.php, v 1.1 2007/11/04 14:29:09 gobal ...
Exp $
```

3 /**

 * @file book-node-export-html.tpl.php

 * Default theme implementation for rendering a single node in a ...

 * printer

 * friendly outline.

8 *

 * @see book-node-export-html.tpl.php

 * Where it is collected and printed out.

 *

 * Available variables:

13 * - \$depth: Depth of the current node inside the outline.

 * - \$title: Node title.

 * - \$content: Node content.

 * - \$children: All the child nodes recursively rendered through this ...

 * file.

 *

18 * @see template_preprocess_book_node_export_html()

 */

?>

<div id="node-<?php print \$node->nid; ?>" class="section-<?php print ...

 \$depth; ?>">

 <h1 class="book-heading"><?php print \$title; ?></h1>

 <?php print \$content; ?>

23 |

```
| <?php print $children; ?>
| </div>
```

Capítulo 5

Carpeta drupal/modules/comment

5.1. Fichero comment-folded.tpl.php

```
<?php
// $Id: comment-folded.tpl.php, v 1.2 2007/08/07 08:39:35 gobal Exp $

/**
 * @file comment-folded.tpl.php
 * Default theme implementation for folded comments.
 *
 * Available variables:
 * - $title: Linked title to full comment.
 * - $new: New comment marker.
 * - $author: Comment author. Can be link or plain text.
 * - $date: Date and time of posting.
 * - $comment: Full comment object.
 *
 * @see template_preprocess_comment_folded()
 * @see theme_comment_folded()
 */
?>
<div class="comment-folded">
    <span class="subject"><?php print $title . ' ' . $new; ?></span><span ...
        class="credit"><?php print t('by') . ' ' . $author; ?></span>
</div>
```

5.2. Fichero comment.tpl.php

```
<?php
// $Id: comment.tpl.php, v 1.4.2.1 2008/03/21 21:58:28 gobal Exp $

/**
 * @file comment.tpl.php
 * Default theme implementation for comments.
 *
```

```

9   * Available variables:
* - $author: Comment author. Can be link or plain text.
* - $content: Body of the post.
* - $date: Date and time of posting.
* - $links: Various operational links.
* - $new: New comment marker.
14  * - $picture: Authors picture.
* - $signature: Authors signature.
* - $status: Comment status. Possible values are:
*   comment-unpublished, comment-published or comment-preview.
* - $submitted: By line with date and time.
19  * - $title: Linked title.

*
* These two variables are provided for context.
* - $comment: Full comment object.
* - $node: Node object the comments are attached to.
24 *
* @see template_preprocess_comment()
* @see theme_comment()
*/
?>
29 <div class="comment<?php print ($comment->new) ? ' comment-new' : ''; ...
      print '$status ?> clear-block">
      <?php print $picture ?>

      <?php if ($comment->new): ?>
          <span class="new"><?php print $new ?></span>
34      <?php endif; ?>

      <h3><?php print $title ?></h3>

      <div class="submitted">
          <?php print $submitted ?>
      </div>

      <div class="content">
          <?php print $content ?>
39          <?php if ($signature): ?>
              <div class="user-signature clear-block">
                  <?php print $signature ?>
              </div>
              <?php endif; ?>
49          </div>

          <?php print $links ?>
      </div>

```

5.3. Fichero comment-wrapper.tpl.php

```

<?php
// $Id: comment-wrapper.tpl.php, v 1.2 2007/08/07 08:39:35 gobal Exp $3

```

```
/*
 *  @file comment-wrapper.tpl.php
 *  Default theme implementation to wrap comments.
 *
8 * Available variables:
 * - $content: All comments for a given page. Also contains sorting ...
   controls
 *   and comment forms if the site is configured for it.
 *
 * The following variables are provided for contextual information.
13 * - $node: Node object the comments are attached to.
 * The constants below the variables show the possible values and ...
   should be
 * used for comparison.
 * - $display_mode
 *   - COMMENT_MODE_FLAT_COLLAPSED
18 *   - COMMENT_MODE_FLAT_EXPANDED
 *   - COMMENT_MODE_THREADED_COLLAPSED
 *   - COMMENT_MODE_THREADED_EXPANDED
 * - $display_order
 *   - COMMENT_ORDER_NEWEST_FIRST
23 *   - COMMENT_ORDER_OLDEST_FIRST
 * - $comment_controls_state
 *   - COMMENT_CONTROLS_ABOVE
 *   - COMMENT_CONTROLS_BELOW
 *   - COMMENT_CONTROLS_ABOVE_BELOW
28 *   - COMMENT_CONTROLS_HIDDEN
 *
 * @see template_preprocess_comment_wrapper()
 * @see theme_comment_wrapper()
 */
33 ?>
<div id="comments">
  <?php print $content; ?>
</div>
```

Capítulo 6

Carpeta drupal/modules/forum

6.1. Fichero forum-icon.tpl.php

```
<?php
// $Id: forum-icon.tpl.php, v 1.3 2007/12/20 09:35:09 gobal Exp $

4 /**
 * @file forum-icon.tpl.php
 * Display an appropriate icon for a forum post.
 *
 * Available variables:
9 * - $new_posts: Indicates whether or not the topic contains new posts...
 *
 * - $icon: The icon to display. May be one of 'hot', 'hot-new', 'new...
14 *      , 'default', 'closed', or 'sticky'.
 *
 * @see template_preprocess_forum_icon()
 * @see theme_forum_icon()
 */
?>
<?php if ($new_posts): ?>
    <a name="new">
19 <?php endif; ?>

<?php print theme('image', "misc/forum-$icon.png") ?>
<?php if ($new_posts): ?>
24     </a>
<?php endif; ?>
```

6.2. Fichero forum-list.tpl.php

```
<?php
// $Id: forum-list.tpl.php, v 1.4 2007/08/30 18:58:12 gobal Exp $
```

```

5  /**
6   *  @file forum-list.tpl.php
7   *  Default theme implementation to display a list of forums and ...
8   *  containers.
9   *
10  * Available variables:
11  * - $forums: An array of forums and containers to display. It is ...
12  *   keyed to the
13  *   numeric id's of all child forums and containers.
14  * - $forum_id: Forum id for the current forum. Parent to all items ...
15  *   within
16  *   the $forums array.
17  *
18  * Each $forum in $forums contains:
19  * - $forum->is_container: Is TRUE if the forum can contain other ...
20  *   forums. Is
21  *   FALSE if the forum can contain only topics.
22  * - $forum->depth: How deep the forum is in the current hierarchy.
23  * - $forum->zebra: 'even' or 'odd' string used for row class.
24  * - $forum->name: The name of the forum.
25  * - $forum->link: The URL to link to this forum.
26  * - $forum->description: The description of this forum.
27  * - $forum->new_topics: True if the forum contains unread posts.
28  * - $forum->new_url: A URL to the forum's unread posts.
29  * - $forum->new_text: Text for the above URL which tells how many new...
30  *   posts.
31  * - $forum->old_topics: A count of posts that have already been read.
32  * - $forum->num_posts: The total number of posts in the forum.
33  * - $forum->last_reply: Text representing the last time a forum was ...
34  *   posted or
35  *   commented in.
36  *
37  * @see template_preprocess_forum_list()
38  * @see theme_forum_list()
39  */
40 ?>
41 <table id="forum-<?php print $forum_id; ?>">
42   <thead>
43     <tr>
44       <th><?php print t('Forum'); ?></th>
45       <th><?php print t('Topics');?></th>
46       <th><?php print t('Posts'); ?></th>
47       <th><?php print t('Last post'); ?></th>
48     </tr>
49   </thead>
50   <tbody>
51     <?php foreach ($forums as $child_id => $forum): ?>
52       <tr id="forum-list-<?php print $child_id; ?>" class="<?php print ...
53         $forum->zebra; ?>">
54         <td <?php print $forum->is_container ? 'colspan="4" class="...
55           container"' : 'class="forum"'; ?>>
56           <?php /* Enclose the contents of this cell with X divs, where ...
57             X is the

```

```

      * depth this forum resides at. This will allow us to ...
use CSS
      * left-margin for indenting.
50   /*?>
<?php print str_repeat('<div class="indent">', $forum->depth);?>
      <div class="name"><a href="<?php print $forum->link; ?>"><?...
php print $forum->name; ?></a></div>
      <?php if ($forum->description): ?>
          <div class="description"><?php print $forum->description; ...?></div>
55      <?php endif; ?>
          <?php print str_repeat('</div>', $forum->depth); ?>
</td>
      <?php if (!$forum->is_container): ?>
          <td class="topics">
60          <?php print $forum->num_topics ?>
          <?php if ($forum->new_topics): ?>
              <br />
              <a href="<?php print $forum->new_url; ?>"><?php print ...$forum->new_text; ?></a>
              <?php endif; ?>
65          </td>
          <td class="posts"><?php print $forum->num_posts ?></td>
          <td class="last-reply"><?php print $forum->last_reply ?></td>
          <?php endif; ?>
</tr>
70      <?php endforeach; ?>
</tbody>
</table>

```

6.3. Fichero forums.tpl.php

```

<?php
// $Id: forums.tpl.php, v 1.4 2007/08/07 08:39:35 gobal Exp $
3 /**
 * @file forums.tpl.php
 * Default theme implementation to display a forum which may contain ...
 * forum
 * containers as well as forum topics.
8 *
 * Variables available:
 * - $links: An array of links that allow a user to post new forum ...
 * topics.
 * It may also contain a string telling a user they must log in in ...
 * order
 * to post.
13 * - $forums: The forums to display (as processed by forum-list.tpl....
 * php)
 * - $topics: The topics to display (as processed by forum-topic-list.....
 * tpl.php)

```

```

18    * - $forums_defined: A flag to indicate that the forums are ...
      * configured .
      *
      * @see template_preprocess_forums()
      * @see theme_forums()
      */
?>
<?php if ($forums_defined): ?>
<div id="forum">
23   <?php print theme('links', $links); ?>
   <?php print $forums; ?>
   <?php print $topics; ?>
</div>
<?php endif; ?>
```

6.4. Fichero forum-submitted.tpl.php

```

<?php
// $Id: forum-submitted.tpl.php, v 1.3 2007/08/07 08:39:35 gobal Exp $
```

3 /**
 * @file forum-submitted.tpl.php
 * Default theme implementation to format a simple string indicated ...
 * when and
 * by whom a topic was submitted.

8 *
 * Available variables:
 *

13 * - \$author: The author of the post.
 * - \$time: How long ago the post was created.
 * - \$topic: An object with the raw data of the post. Unsafe, be sure
 * to clean this data before printing.
 *

18 * @see template_preprocess_forum_submitted()
 * @see theme_forum_submitted()
 */

?>
<?php if (\$time): ?>
<?php print t(
 '@time ago
by !author', array(
 '@time' => \$time,
 '!author' => \$author,
 23)); ?>
<?php else: ?>
 <?php print t('n/a'); ?>
<?php endif; ?>

28

6.5. Fichero forum-topic-list.tpl.php

```

<?php
// $Id: forum-topic-list.tpl.php, v 1.4.2.1 2008/10/22 18:22:51 dries ...
Exp $


/**
 * @file forum-topic-list.tpl.php
 * Theme implementation to display a list of forum topics.
 *
 * Available variables:
 * - $header: The table header. This is pre-generated with click-...
 *   sorting
 * information. If you need to change this, @see ...
 * template_preprocess_forum_topic_list().
 * - $pager: The pager to display beneath the table.
 * - $topics: An array of topics to be displayed.
 * - $topic_id: Numeric id for the current forum topic.
 *
 * Each $topic in $topics contains:
 * - $topic->icon: The icon to display.
 * - $topic->moved: A flag to indicate whether the topic has been ...
 *   moved to
 *   another forum.
 * - $topic->title: The title of the topic. Safe to output.
 * - $topic->message: If the topic has been moved, this contains an
 *   explanation and a link.
 * - $topic->zebra: 'even' or 'odd' string used for row class.
 * - $topic->num_comments: The number of replies on this topic.
 * - $topic->new_replies: A flag to indicate whether there are unread ...
 *   comments.
 * - $topic->new_url: If there are unread replies, this is a link to ...
 *   them.
 * - $topic->new_text: Text containing the translated, properly ...
 *   pluralized count.
 * - $topic->created: An outputtable string represented when the topic...
 *   was posted.
 * - $topic->last_reply: An outputtable string representing when the ...
 *   topic was
 *   last replied to.
 * - $topic->timestamp: The raw timestamp this topic was posted.
 *
 * @see template_preprocess_forum_topic_list()
 * @see theme_forum_topic_list()
 */
?>
<table id="forum-topic-php print $topic_id; ?&gt;"&gt;
  &lt;thead&gt;
    &lt;tr&gt;&lt;?php print $header; ?&gt;&lt;/tr&gt;
  &lt;/thead&gt;
  &lt;tbody&gt;
    &lt;?php foreach ($topics as $topic): ?&gt;
      &lt;tr class="<?php print $topic-&gt;zebra;?&gt;"&gt;
        &lt;td class="icon"&gt;&lt;?php print $topic-&gt;icon; ?&gt;&lt;/td&gt;
        &lt;td class="title"&gt;&lt;?php print $topic-&gt;title; ?&gt;&lt;/td&gt;
</pre

```

```

47    <?php if ($topic->moved): ?>
48        <td colspan="3"><?php print $topic->message; ?></td>
49    <?php else: ?>
50        <td class="replies">
51            <?php print $topic->num_comments; ?>
52            <?php if ($topic->new_replies): ?>
53                <br />
54                <a href="php print $topic-&gt;new_url; ?&gt;"&gt;&lt;?php print $topic ...
55                    -&gt;new_text; ?&gt;&lt;/a&gt;
56                &lt;?php endif; ?&gt;
57            &lt;/td&gt;
58            &lt;td class="created"&gt;&lt;?php print $topic-&gt;created; ?&gt;&lt;/td&gt;
59            &lt;td class="last-reply"&gt;&lt;?php print $topic-&gt;last_reply; ?&gt;&lt;/td&gt;
60            &lt;?php endif; ?&gt;
61        &lt;/tr&gt;
62    &lt;?php endforeach; ?&gt;
63    &lt;/tbody&gt;
64&lt;/table&gt;
65&lt;?php print $pager; ?&gt;
</pre

```

6.6. Fichero forum-topic-navigation.tpl.php

```

<?php
// $Id: forum-topic-navigation.tpl.php, v 1.2 2007/08/07 08:39:35 gobal ...
Exp $

3 /**
 * @file forum-topic-navigation.tpl.php
 * Default theme implementation to display the topic navigation string...
 * at the
 * bottom of all forum topics.
8 *
 * Available variables:
 *
 * - $prev: The node ID of the previous post.
 * - $prev_url: The URL of the previous post.
13 * - $prev_title: The title of the previous post.
 *
 * - $next: The node ID of the next post.
 * - $next_url: The URL of the next post.
 * - $next_title: The title of the next post.
18 *
 * - $node: The raw node currently being viewed. Contains unsafe data
 * and any data in this must be cleaned before presenting.
 *
 * @see template_preprocess_forum_topic_navigation()
 * @see theme_forum_topic_navigation()
*/
?>
<?php if ($prev || $next): ?>
<div class="forum-topic-navigation clear-block">
    <?php if ($prev): ?>

```

```
33 |     <a href="php print $prev_url; ?&gt;" class="topic-previous" title...<br/|     ="<?php print t('Go to previous forum topic') ?>">    <?php print ...  
|     $prev_title ?></a>  
|     <?php endif; ?>  
|     <?php if ($next): ?>  
|         <a href="php print $next_url; ?&gt;" class="topic-next" title="<?...<br/|             php print t('Go to next forum topic') ?>"><?php print $next_title ...  
|         ?>      </a>  
|         <?php endif; ?>  
|     </div>  
|     <?php endif; ?>
```

Capítulo 7

Carpeta drupal/modules/node

7.1. Fichero node.tpl.php

```
<?php
// $Id: node.tpl.php, v 1.4.2.1 2009/08/10 10:48:33 gobal Exp $

/*
5 * @file node.tpl.php
*
* Theme implementation to display a node.
*
* Available variables:
10 * - $title: the (sanitized) title of the node.
* - $content: Node body or teaser depending on $teaser flag.
* - $picture: The authors picture of the node output from
*   theme_user_picture().
* - $date: Formatted creation date (use $created to reformat with
15 *   format_date()).
* - $links: Themed links like "Read more", "Add new comment", etc. ...
*   output
*   from theme_links().
* - $name: Themed username of node author output from theme_username...
*   ().
* - $node_url: Direct url of the current node.
20 * - $terms: the themed list of taxonomy term links output from ...
*   theme_links().
* - $submitted: themed submission information output from
*   theme_node_submitted().
*
* Other variables:
25 * - $node: Full node object. Contains data that may not be safe.
* - $type: Node type, i.e. story, page, blog, etc.
* - $comment_count: Number of comments attached to the node.
* - $uid: User ID of the node author.
* - $created: Time the node was published formatted in Unix timestamp...
*
30 * - $zebra: Outputs either "even" or "odd". Useful for zebra striping...
*   in
*   teaser listings.
* - $id: Position of the node. Increments each time it's output.
```

```

*
 * Node status variables:
35 * - $teaser: Flag for the teaser state.
* - $page: Flag for the full page state.
* - $promote: Flag for front page promotion state.
* - $sticky: Flags for sticky post setting.
* - $status: Flag for published status.
40 * - $comment: State of comment settings for the node.
* - $readmore: Flags true if the teaser content of the node cannot ...
    hold the
*     main body content.
* - $is_front: Flags true when presented in the front page.
* - $logged_in: Flags true when the current user is a logged-in ...
    member.
45 * - $is_admin: Flags true when the current user is an administrator.
*
* @see template_preprocess()
* @see template_preprocess_node()
*/
50?>
<div id="node-<?php print $node->nid; ?>" class="node<?php if ($sticky...
    ) { print ' sticky'; } ?><?php if (!$status) { print ' node-...
    unpublished'; } ?> clear-block">

<?php print $picture ?>

55<?php if (!$page): ?>
    <h2><a href="<?php print $node_url ?>" title="<?php print $title ?>"...
        ><?php print $title ?></a></h2>
    <?php endif; ?>

    <div class="meta">
60    <?php if ($submitted): ?>
        <span class="submitted"><?php print $submitted ?></span>
    <?php endif; ?>

    <?php if ($terms): ?>
65        <div class="terms terms-inline"><?php print $terms ?></div>
    <?php endif;?>
    </div>

    <div class="content">
70        <?php print $content ?>
    </div>

    <?php print $links; ?>
</div>

```

Capítulo 8

Carpeta drupal/modules/poll

8.1. Fichero poll-bar-block.tpl.php

```
1 <?php
// $Id: poll-bar-block.tpl.php, v 1.2 2007/08/07 08:39:35 gobal Exp $

/*
 * @file poll-bar-block.tpl.php
 * Display the bar for a single choice in a poll
 *
 * Variables available:
 * - $title: The title of the poll.
 * - $votes: The number of votes for this choice
11 * - $total_votes: The number of votes for this choice
 * - $percentage: The percentage of votes for this choice.
 * - $vote: The choice number of the current user's vote.
 * - $voted: Set to TRUE if the user voted for this choice.
 *
16 * @see template_preprocess_poll_bar()
 */
?>

<div class="text"><?php print $title; ?></div>
21 <div class="bar">
    <div style="width: <?php print $percentage; ?>%;" class="foreground"...
        ></div>
    </div>
    <div class="percent">
        <?php print $percentage; ?>%
26 </div>
```

8.2. Fichero poll-bar.tpl.php

```
<?php
// $Id: poll-bar.tpl.php, v 1.2 2007/08/07 08:39:35 gobal Exp $

4 /**
 * @file poll-bar.tpl.php
```

```

    * Display the bar for a single choice in a poll
    *
    * Variables available:
9   * - $title: The title of the poll.
    * - $votes: The number of votes for this choice
    * - $total_votes: The number of votes for this choice
    * - $percentage: The percentage of votes for this choice.
    * - $vote: The choice number of the current user's vote.
14  * - $voted: Set to TRUE if the user voted for this choice.
    *
    * @see template_preprocess_poll_bar()
*/
?>
19 <div class="text"><?php print $title; ?></div>
<div class="bar">
    <div style="width: <?php print $percentage; ?>%;" class="foreground"...
        ></div>
</div>
24 <div class="percent">
    <?php print $percentage; ?>% (<?php print format_plural($votes, '1 ...
        vote', '@count votes'); ?>)
</div>

```

8.3. Fichero poll-results-block.tpl.php

```

<?php
// $Id: poll-results-block.tpl.php, v 1.2 2007/08/02 20:08:53 dries Exp...
$ 
/** 
 * @file poll-results-block.tpl.php
 * Display the poll results in a block.
 *
 * Variables available:
 * - $title: The title of the poll.
9  * - $results: The results of the poll.
    * - $votes: The total results in the poll.
    * - $links: Links in the poll.
    * - $nid: The nid of the poll
    * - $cancel_form: A form to cancel the user's vote, if allowed.
14  * - $raw_links: The raw array of links. Should be run through theme('...
        links')
    * if used.
    * - $vote: The choice number of the current user's vote.
    *
    * @see template_preprocess_poll_results()
19 */
?>

<div class="poll">
    <div class="title"><?php print $title ?></div>
    <?php print $results ?>

```

```

<div class="total">
  <?php print t('Total votes: @votes', array('@votes' => $votes)); ...
?
</div>
</div>
29<div class="links"><?php print $links; ?></div>

```

8.4. Fichero poll-results.tpl.php

```

1<?php
// $Id: poll-results.tpl.php, v 1.2 2007/08/07 08:39:35 goba Exp $

/**
 * @file poll-results-block.tpl.php
6 * Display the poll results in a block.
*
* Variables available:
* - $title: The title of the poll.
* - $results: The results of the poll.
11* - $votes: The total results in the poll.
* - $links: Links in the poll.
* - $nid: The nid of the poll
* - $cancel_form: A form to cancel the user's vote, if allowed.
* - $raw_links: The raw array of links.
16* - $vote: The choice number of the current user's vote.
*
* @see template_preprocess_poll_results()
*/
?>
21<div class="poll">
  <?php print $results; ?>
  <div class="total">
    <?php print t('Total votes: @votes', array('@votes' => $votes)); ...
?
  </div>
26  <?php if (!empty($cancel_form)): ?>
    <?php print $cancel_form; ?>
    <?php endif; ?>
  </div>

```

8.5. Fichero poll-vote.tpl.php

```

1<?php
// $Id: poll-vote.tpl.php, v 1.2 2007/08/07 08:39:35 goba Exp $
6 /**
 * @file poll-vote.tpl.php
 * Voting form for a poll.
*
```

```
11    * - $choice: The radio buttons for the choices in the poll.  
11    * - $title: The title of the poll.  
11    * - $block: True if this is being displayed as a block.  
11    * - $vote: The vote button  
11    * - $rest: Anything else in the form that may have been added via  
11      form_alter hooks.  
11    *  
11    * @see template_preprocess_poll_vote()  
16   */  
?>  
<div class="poll">  
  <div class="vote-form">  
    <div class="choices">  
      21      <?php if ($block): ?>  
      21      <div class="title"><?php print $title; ?></div>  
      21      <?php endif; ?>  
      21      <?php print $choice; ?>  
      21      </div>  
      26      <?php print $vote; ?>  
    </div>  
    <?php // This is the 'rest' of the form, in case items have been ...  
    added. ?>  
    <?php print $rest ?>  
</div>
```

Capítulo 9

Carpeta drupal/modules/profile

9.1. Fichero profile-block.tpl.php

```
<?php
// $Id: profile-block.tpl.php, v 1.2 2007/08/07 08:39:35 goba Exp $

/**
 * @file profile-block.tpl.php
 * Default theme implementation for displaying a users profile within ...
 * a
 * block. It only shows in relation to a node displayed as a full page...
 *
 * Available variables:
 * - $picture: Image configured for the account linking to the users ...
 *   page.
 * - $profile: Keyed array of all profile fields that have a value.
 *
 * Each $field in $profile contains:
 * - $field->title: Title of the profile field.
 * - $field->value: Value of the profile field.
 * - $field->type: Type of the profile field, i.e., checkbox, ...
 *   textfield,
 *   textarea, selection, list, url or date.
 *
 * Since $profile is keyed, a direct print of the field is possible. ...
 * Not
 * all accounts may have a value for a profile so do a check first. If...
 * a field
 * of "last_name" was set for the site, the following can be used.
 *
 * <?php if (isset($profile['last_name'])): ?>
 *   <div class="field last-name">
 *     <?php print $profile['last_name']->title; ?>:<br />
 *     <?php print $profile['last_name']->value; ?>
 *   </div>
 * <?php endif; ?>
```

```

30  *
31  * @see template_preprocess_profile_block()
32  */
33 ?>
34 <?php print $picture; ?>
35 <?php foreach ($profile as $field) : ?>
36   <p>
37     <?php if ($field->type != 'checkbox') : ?>
38       <strong><?php print $field->title; ?></strong><br />
39     <?php endif; ?>
40     <?php print $field->value; ?>
41   </p>
42 <?php endforeach; ?>

```

9.2. Fichero profile-listing.tpl.php

```

<?php
// $Id: profile-listing.tpl.php, v 1.2 2007/08/07 08:39:35 goba Exp $

3 /**
4  * @file profile-listing.tpl.php
5  * Default theme implementation for displaying a user and their ...
6  * profile data
7  * for member listing pages.
8 *
9  * @see profile-wrapper.tpl.php
10 *      where all the data is collected and printed out.
11 *
12 * Available variables:
13 * - $picture: Image configured for the account linking to the users ...
14 *               page.
15 * - $name: User's account name linking to the users page.
16 * - $profile: Keyed array of all profile fields that are set as ...
17 *               visible
18 *               in member list pages (configured by site administrators). It also...
19 *               needs
20 *               to have a value in order to be present.
21 *
22 * Each $field in $profile contains:
23 * - $field->title: Title of the profile field.
24 * - $field->value: Value of the profile field.
25 * - $field->type: Type of the profile field, i.e., checkbox, ...
26 *                textfield,
27 *                 textarea, selection, list, url or date.
28 *
29 * Since $profile is keyed, a direct print of the field is possible. ...
30 * Not
31 * all accounts may have a value for a profile so do a check first. If...
32 * a field
33 * of "last_name" was set for the site, the following can be used.
34 *
35

```

```

*   <?php if (isset($profile['last_name'])): ?>
*       <div class="field last-name">
*           <?php print $profile['last_name']->title; ?:<br />
*           <?php print $profile['last_name']->value; ?>
33     </div>
*   <?php endif; ?>
*
* @see template_preprocess_profile_listing()
*/
38 ?>
<div class="profile">
    <?php print $picture; ?>

    <div class="name">
        <?php print $name; ?>
    </div>

    <?php foreach ($profile as $field) : ?>
        <div class="field">
            <?php print $field->value; ?>
        </div>
48     <?php endforeach; ?>

</div>

```

9.3. Fichero profile-wrapper.tpl.php

```

<?php
// $Id: profile-wrapper.tpl.php, v 1.2 2007/08/07 08:39:35 goba Exp $

3 /**
 * @file profile-wrapper.tpl.php
 * Default theme implementation for wrapping member listings and their
 * profiles.
8 *
* This template is used when viewing a list of users. It can be a ...
* general
* list for viewing all users with the url of "example.com/profile" or...
* when
* viewing a set of users who share a specific value for a profile ...
* such
* as "example.com/profile/country/belgium".
13 *
* Available variables:
* - $content: User account profiles iterated through profile-listing....
* tpl.php.
* - $current_field: The named field being browsed. Provided here for ...
* context.
* The above example would result in "last_name". An alternate ...
* template name
18 * is also based on this, e.g., "profile-wrapper-last_name.tpl.php".
*
```

```
* @see template_preprocess_profile_wrapper()
*/
?>
23<div id="profile">
    <?php print $content; ?>
</div>
```

Capítulo 10

Carpeta drupal/modules/search

10.1. Fichero search-block-form.tpl.php

```
<?php
// $Id: search-block-form.tpl.php, v 1.1 2007/10/31 18:06:38 dries Exp ...
§

/**
 * @file search-block-form.tpl.php
 * Default theme implementation for displaying a search form within a ...
 * block region.
 *
 * Available variables:
 * - $search_form: The complete search form ready for print.
 * - $search: Array of keyed search elements. Can be used to print ...
 *   each form
 *   element separately.
 *
 * Default keys within $search:
 * - $search['search_block_form']: Text input area wrapped in a div.
 * - $search['submit']: Form submit button.
 * - $search['hidden']: Hidden form elements. Used to validate forms ...
 *   when submitted.
 *
 * Since $search is keyed, a direct print of the form element is ...
 *   possible.
 * Modules can add to the search form so it is recommended to check ...
 *   for their
20 * existence before printing. The default keys will always exist.
 *
 * <?php if (isset($search['extra_field'])): ?>
 *   <div class="extra-field">
 *     <?php print $search['extra_field']; ?>
25 *   </div>
 * <?php endif; ?>
 *
 * To check for all available data within $search, use the code below.
```

```

30  *
31  *      <?php print '<pre>'. check_plain(print_r($search, 1)) . '</pre>'; ...
32  *
33  *      *
34  *      @see template_preprocess_search_block_form()
35  */
36 ?>
37 <div class="container-inline">
38     <?php print $search_form; ?>
39 </div>

```

10.2. Fichero search-results.tpl.php

```

<?php
// $Id: search-results.tpl.php, v 1.1 2007/10/31 18:06:38 dries Exp $

3 /**
4  * @file search-results.tpl.php
5  * Default theme implementation for displaying search results.
6  *
7  * This template collects each invocation of theme_search_result(). ...
8  * This and
9  * the child template are dependant to one another sharing the markup ...
10 * for
11 * definition lists.
12 *
13 * Note that modules may implement their own search type and theme ...
14 * function
15 * completely bypassing this template.
16 *
17 * Available variables:
18 * - $search_results: All results as it is rendered through
19 *   search-result.tpl.php
20 * - $type: The type of search, e.g., "node" or "user".
21 *
22 *
23 *      @see template_preprocess_search_results()
24 */
25 ?>
26 <dl class="search-results <?php print $type; ?>-results">
27     <?php print $search_results; ?>
28 </dl>
29 <?php print $pager; ?>

```

10.3. Fichero search-result.tpl.php

```

<?php
// $Id: search-result.tpl.php, v 1.1.2.1 2008/08/28 08:21:44 dries Exp ...

```

```

3 | /**
4 | * @file search-result.tpl.php
5 | * Default theme implementation for displaying a single search result.
6 |
7 | * This template renders a single search result and is collected into
8 | * search-results.tpl.php. This and the parent template are
9 | * dependent to one another sharing the markup for definition lists.
10| *
11| * Available variables:
12| * - $url: URL of the result.
13| * - $title: Title of the result.
14| * - $snippet: A small preview of the result. Does not apply to user ...
15| *   searches.
16| * - $info: String of all the meta information ready for print. Does ...
17| *   not apply
18| *   to user searches.
19| * - $info_split: Contains same data as $info, split into a keyed ...
20| *   array.
21| * - $type: The type of search, e.g., "node" or "user".
22| *
23| * Default keys within $info_split:
24| * - $info_split['type']: Node type.
25| * - $info_split['user']: Author of the node linked to users profile. ...
26| *   Depends
27| *   on permission.
28| * - $info_split['date']: Last update of the node. Short formatted.
29| * - $info_split['comment']: Number of comments output as "% comments...
30| *   %"
31| *   being the count. Depends on comment.module.
32| * - $info_split['upload']: Number of attachments output as "% ...
33| *   attachments", %
34| *   being the count. Depends on upload.module.
35| *
36| * Since $info_split is keyed, a direct print of the item is possible.
37| * This array does not apply to user searches so it is recommended to ...
38| *   check
39| * for their existance before printing. The default keys of 'type', '...
40| *   user' and
41| *   'date' always exist for node searches. Modules may provide other ...
42| *   data.
43| *
44| * <?php if (isset($info_split['comment'])) : ?>
45| *   <span class="info-comment">
46| *     <?php print $info_split['comment']; ?>
47| *   </span>
48| * <?php endif; ?>
49| *
50| * To check for all available data within $info_split, use the code ...
51| *   below.
52| *
53| * <?php print '<pre>'. check_plain(print_r($info_split, 1)).'</pre...
54| *   >'; ?>
55| *

```

```

1   * @see template_preprocess_search_result()
2   */
3 ?>
4 <dt class="title">
5   <a href="<?php print $url; ?>"><?php print $title; ?></a>
6 </dt>
7 <dd>
8   <?php if ($snippet) : ?>
9     <p class="search-snippet"><?php print $snippet; ?></p>
10    <?php endif; ?>
11    <?php if ($info) : ?>
12      <p class="search-info"><?php print $info; ?></p>
13    <?php endif; ?>
14  </dd>
15

```

10.4. Fichero search-theme-form.tpl.php

```

1 <?php
2 // $Id: search-theme-form.tpl.php, v 1.1 2007/10/31 18:06:38 dries Exp ...
3
4 /**
5  * @file search-theme-form.tpl.php
6  * Default theme implementation for displaying a search form directly ...
7  * into the
8  * theme layout. Not to be confused with the search block or the ...
9  * search page.
10 *
11 * Available variables:
12 * - $search_form: The complete search form ready for print.
13 * - $search: Array of keyed search elements. Can be used to print ...
14 *   each form
15 *   element separately.
16 *
17 * Default keys within $search:
18 * - $search['search_theme_form']: Text input area wrapped in a div.
19 * - $search['submit']: Form submit button.
20 * - $search['hidden']: Hidden form elements. Used to validate forms ...
21 *   when submitted.
22 *
23 * Since $search is keyed, a direct print of the form element is ...
24 * possible.
25 * Modules can add to the search form so it is recommended to check ...
26 *   for their
27 *   existance before printing. The default keys will always exist.
28 *
29 *   <?php if (isset($search['extra_field'])): ?>
30 *     <div class="extra-field">
31 *       <?php print $search['extra_field']; ?>
32 *     </div>
33 *   <?php endif; ?>
34 *

```

```
31    * To check for all available data within $search, use the code below.  
31    *  
31    *      <?php print '<pre>'. check_plain(print_r($search, 1)) . '</pre>'; ...  
31    *  
31    * @see template_preprocess_search_theme_form()  
31    */  
31 ?>  
36<div id="search" class="container-inline">  
36    <?php print $search_form; ?>  
36</div>
```

Capítulo 11

Carpeta drupal/modules/system

11.1. Fichero block.tpl.php

```
<?php
// $Id: block.tpl.php, v 1.4 2007/09/01 05:42:48 dries Exp $

/**
 * @file block.tpl.php
 *
 * Theme implementation to display a block.
 *
 * Available variables:
 * - $block->subject: Block title.
 * - $block->content: Block content.
 * - $block->module: Module that generated the block.
 * - $block->delta: This is a numeric id connected to each module.
 * - $block->region: The block region embedding the current block.
 *
 * Helper variables:
 * - $block_zebra: Outputs 'odd' and 'even' dependent on each block ...
 *   region.
 * - $zebra: Same output as $block_zebra but independent of any block ...
 *   region.
 * - $block_id: Counter dependent on each block region.
 * - $id: Same output as $block_id but independent of any block region...
 *
 * - $is_front: Flags true when presented in the front page.
 * - $logged_in: Flags true when the current user is a logged-in ...
 *   member.
 * - $is_admin: Flags true when the current user is an administrator.
 *
 * @see template_preprocess()
 * @see template_preprocess_block()
 */
?>
<div id="block-<?php print $block->module . '-' . $block->delta; ?>" ...
     class="block block-<?php print $block->module ?>">
```

```

32  <?php if ($block->subject): ?>
    <h2><?php print $block->subject ?></h2>
<?php endif;?>

37  <div class="content">
    <?php print $block->content ?>
</div>

```

11.2. Fichero box.tpl.php

```

3   <?php
// $Id: box.tpl.php, v 1.3 2007/12/16 21:01:45 gobal Exp $
4
5 /**
 * @file box.tpl.php
 *
 * Theme implementation to display a box.
6 *
 * Available variables:
 * - $title: Box title.
 * - $content: Box content.
 *
13 * @see template_preprocess()
 */
?>
<div class="box">

18 <?php if ($title): ?>
    <h2><?php print $title ?></h2>
<?php endif; ?>

23  <div class="content"><?php print $content ?></div>

```

11.3. Fichero maintenance-page.tpl.php

```

2   <?php
// $Id: maintenance-page.tpl.php, v 1.2.2.1 2009/04/30 00:13:31 gobal ...
3   Exp $

4 /**
 * @file maintenance-page.tpl.php
 *
7 * Theme implementation to display a single Drupal page while off-line...
8 *
9 * All the available variables are mirrored in page.tpl.php. Some may ...
10 * be left

```

```

* blank but they are provided for consistency.
*
12 *
* @see template_preprocess()
* @see template_preprocess_maintenance_page()
*/
?>
17 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
    "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="php print ...
    $language-&gt;language ?&gt;" lang="<?php print $language-&gt;language ?&gt;" ...
    dir="<?php print $language-&gt;dir ?&gt;"&gt;

&lt;head&gt;
22     &lt;?php print $head; ?&gt;
        &lt;title&gt;&lt;?php print $head_title; ?&gt;&lt;/title&gt;
        &lt;?php print $styles; ?&gt;
        &lt;?php print $scripts; ?&gt;
        &lt;script type="text/javascript"&gt;&lt;?php /* Needed to avoid Flash of ...
            Unstyled Content in IE */ ?&gt; &lt;/script&gt;
27 &lt;/head&gt;
&lt;body class="<?php print $body_classes; ?&gt;"&gt;
    &lt;div id="page"&gt;
        &lt;div id="header"&gt;
            &lt;div id="logo-title"&gt;
32             &lt;?php if (!empty($logo)) : ?&gt;
                &lt;a href="<?php print $base_path; ?&gt;" title="<?php print t('...
                    Home'); ?&gt;" rel="home" id="logo"&gt;
                    &lt;img src="<?php print $logo; ?&gt;" alt="<?php print t('Home...
                    '); ?&gt;" /&gt;
                &lt;/a&gt;
            &lt;?php endif; ?&gt;
37
            &lt;div id="name-and-slogan"&gt;
                &lt;?php if (!empty($site_name)) : ?&gt;
                    &lt;h1 id="site-name"&gt;
42                     &lt;a href="<?php print $base_path ?&gt;" title="<?php print t...
                        ('Home'); ?&gt;" rel="home"&gt;&lt;span&gt;&lt;?php print $site_name; ?&gt;&lt;/span&gt;&lt;/...
                        a&gt;
                    &lt;/h1&gt;
                &lt;?php endif; ?&gt;
47
                &lt;?php if (!empty($site_slogan)) : ?&gt;
                    &lt;div id="site-slogan"&gt;&lt;?php print $site_slogan; ?&gt;&lt;/div&gt;
                &lt;?php endif; ?&gt;
            &lt;/div&gt; &lt;!-- /name-and-slogan --&gt;
        &lt;/div&gt; &lt;!-- /logo-title --&gt;
52
        &lt;?php if (!empty($header)) : ?&gt;
            &lt;div id="header-region"&gt;
                &lt;?php print $header; ?&gt;
            &lt;/div&gt;
        &lt;?php endif; ?&gt;
</pre

```

```

57   </div> <!-- /header -->
58
59   <div id="container" class="clear-block">
60
61     <?php if (!empty($left)): ?>
62       <div id="sidebar-left" class="column sidebar">
63         <?php print $left; ?>
64       </div> <!-- /sidebar-left -->
65     <?php endif; ?>
66
67     <div id="main" class="column"><div id="main-squeeze">
68
69       <div id="content">
70         <?php if (!empty($title)): ?><h1 class="title" id="page...
71           title"><?php print $title; ?></h1><?php endif; ?>
72         <?php if (!empty($messages)): print $messages; endif; ?>
73           <div id="content-content" class="clear-block">
74             <?php print $content; ?>
75           </div> <!-- /content-content -->
76         </div> <!-- /content -->
77
78     </div></div> <!-- /main-squeeze /main -->
79
80     <?php if (!empty($right)): ?>
81       <div id="sidebar-right" class="column sidebar">
82         <?php print $right; ?>
83       </div> <!-- /sidebar-right -->
84     <?php endif; ?>
85
86   </div> <!-- /container -->
87
88   <div id="footer-wrapper">
89     <div id="footer">
90       <?php print $footer_message; ?>
91       <?php if (!empty($footer)): print $footer; endif; ?>
92     </div> <!-- /footer -->
93   </div> <!-- /footer-wrapper -->
94
95   </div> <!-- /page -->
96
97 </body>
</html>

```

11.4. Fichero page.tpl.php

```

<?php
// $Id: page.tpl.php, v 1.11.2.1 2009/04/30 00:13:31 gobal Exp $

/**
 * @file page.tpl.php
 *

```

```

7  * Theme implementation to display a single Drupal page.
*
* Available variables:
*
* General utility variables:
12 * - $base_path: The base URL path of the Drupal installation. At the ...
  very
*   least, this will always default to /.
* - $css: An array of CSS files for the current page.
* - $directory: The directory the theme is located in, e.g. themes/...
  garland or
*   themes/garland/minelli.
17 * - $is_front: TRUE if the current page is the front page. Used to ...
  toggle the mission statement.
* - $logged_in: TRUE if the user is registered and signed in.
* - $is_admin: TRUE if the user has permission to access ...
  administration pages.
*
* Page metadata:
22 * - $language: (object) The language the site is being displayed in.
*   $language->language contains its textual representation.
*   $language->dir contains the language direction. It will either be...
  'ltr' or 'rtl'.
* - $head_title: A modified version of the page title, for use in the...
  TITLE tag.
* - $head: Markup for the HEAD section (including meta tags, keyword ...
  tags, and
27 *   so on).
* - $styles: Style tags necessary to import all CSS files for the ...
  page.
* - $scripts: Script tags necessary to load the JavaScript files and ...
  settings
*   for the page.
* - $body_classes: A set of CSS classes for the BODY tag. This ...
  contains flags
32 *   indicating the current layout (multiple columns, single column), ...
  the current
*   path, whether the user is logged in, and so on.
*
* Site identity:
* - $front_page: The URL of the front page. Use this instead of ...
  $base_path,
37 *   when linking to the front page. This includes the language domain...
  or prefix.
* - $logo: The path to the logo image, as defined in theme ...
  configuration.
* - $site_name: The name of the site, empty when display has been ...
  disabled
*   in theme settings.
* - $site_slogan: The slogan of the site, empty when display has been...
  disabled
42 *   in theme settings.
* - $mission: The text of the site mission, empty when display has ...
  been disabled

```

```

        *      in theme settings .
        *
        * Navigation :
47     * - $search_box: HTML to display the search box , empty if search has ...
        *   been disabled .
        * - $primary_links (array): An array containing primary navigation ...
        *   links for the
        *   site , if they have been configured .
        * - $secondary_links (array): An array containing secondary ...
        *   navigation links for
        *   the site , if they have been configured .
52     *
        * Page content (in order of occurrence in the default page.tpl.php) :
        * - $left: The HTML for the left sidebar .
        *
        * - $breadcrumb: The breadcrumb trail for the current page .
57     * - $title: The page title , for use in the actual HTML content .
        * - $help: Dynamic help text , mostly for admin pages .
        * - $messages: HTML for status and error messages . Should be ...
        *   displayed prominently .
        * - $tabs: Tabs linking to any sub-pages beneath the current page (e....
        *   g. , the view
        *   and edit tabs when displaying a node) .
62     *
        * - $content: The main content of the current Drupal page .
        *
        * - $right: The HTML for the right sidebar .
        *
67     * Footer/closing data :
        * - $feed_icons: A string of all feed icons for the current page .
        * - $footer_message: The footer message as defined in the admin ...
        *   settings .
        * - $footer : The footer region .
        * - $closure: Final closing markup from any modules that have altered...
        *   the page .
72     * This variable should always be output last , after all other ...
        *   dynamic content .
        *
        * @see template_preprocess()
        * @see template_preprocess_page()
        */
77 ?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
  "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="php print ...
  $language-&gt;language ?&gt;" lang="<?php print $language-&gt;language ?&gt;" ...
  dir="<?php print $language-&gt;dir ?&gt;"&gt;

82 &lt;head&gt;
    &lt;?php print $head; ?&gt;
    &lt;title&gt;&lt;?php print $head_title; ?&gt;&lt;/title&gt;
    &lt;?php print $styles; ?&gt;
    &lt;?php print $scripts; ?&gt;
</pre

```

```

87 | <script type="text/javascript"><?php /* Needed to avoid Flash of ...
|   Unstyled Content in IE */ ?> </script>
|</head>
|<body class="<?php print $body_classes; ?>">
|  <div id="page">
|    <div id="header">
|      <div id="logo-title">
|        <?php if (!empty($logo)): ?>
|          <a href="php print $front_page; ?&gt;" title="<?php print t('...
|            Home'); ?&gt;" rel="home" id="logo"&gt;
|            &lt;img src="<?php print $logo; ?&gt;" alt="<?php print t('Home...
|              '); ?&gt;"/&gt;
|          &lt;/a&gt;
|        &lt;?php endif; ?&gt;
|
|        &lt;div id="name-and-slogan"&gt;
|          &lt;?php if (!empty($site_name)): ?&gt;
|            &lt;h1 id="site-name"&gt;
|              &lt;a href="<?php print $front_page ?&gt;" title="<?php print ...
|                t('Home'); ?&gt;" rel="home"&gt;&lt;span&gt;&lt;?php print $site_name; ?&gt;&lt;/span...
|              &gt;&lt;/a&gt;
|            &lt;/h1&gt;
|          &lt;?php endif; ?&gt;
|
|          &lt;?php if (!empty($site_slogan)): ?&gt;
|            &lt;div id="site-slogan"&gt;&lt;?php print $site_slogan; ?&gt;&lt;/div&gt;
|          &lt;?php endif; ?&gt;
|          &lt;/div&gt; &lt;!-- /name-and-slogan --&gt;
|        &lt;/div&gt; &lt;!-- /logo-title --&gt;
|
|        &lt;?php if (!empty($search_box)): ?&gt;
|          &lt;div id="search-box"&gt;&lt;?php print $search_box; ?&gt;&lt;/div&gt;
|        &lt;?php endif; ?&gt;
|
|        &lt;?php if (!empty($header)): ?&gt;
|          &lt;div id="header-region"&gt;
|            &lt;?php print $header; ?&gt;
|          &lt;/div&gt;
|        &lt;?php endif; ?&gt;
|
|      &lt;/div&gt; &lt;!-- /header --&gt;
|
|      &lt;div id="container" class="clear-block"&gt;
|
|        &lt;div id="navigation" class="menu &lt;?php if (!empty($primary_links...
|          )) { print "withprimary"; } if (!empty($secondary_links)) { print ...
|            "withsecondary"; } ?&gt; "&gt;
|          &lt;?php if (!empty($primary_links)): ?&gt;
|            &lt;div id="primary" class="clear-block"&gt;
|              &lt;?php print theme('links', $primary_links, array('class' ...
|                =&gt; 'links_primary-links')) ; ?&gt;
|            &lt;/div&gt;
|          &lt;?php endif; ?&gt;
|
|      &lt;/div&gt;
|    &lt;?php endif; ?&gt;
|  &lt;/div&gt;
|&lt;/body&gt;
</pre

```

```

137      <?php if (!empty($secondary_links)): ?>
138          <div id="secondary" class="clear-block">
139              <?php print theme('links', $secondary_links, array('class'...
140                  => 'links secondary-links'))); ?>
141          </div>
142          <?php endif; ?>
143      </div> <!-- /navigation -->

144      <?php if (!empty($left)): ?>
145          <div id="sidebar-left" class="column sidebar">
146              <?php print $left; ?>
147          </div> <!-- /sidebar-left -->
148      <?php endif; ?>

149      <div id="main" class="column"><div id="main-squeeze">
150          <?php if (!empty($breadcrumb)): ?><div id="breadcrumb"><?php ...
151              print $breadcrumb; ?></div><?php endif; ?>
152              <?php if (!empty($mission)): ?><div id="mission"><?php print ...
153                  $mission; ?></div><?php endif; ?>

154          <div id="content">
155              <?php if (!empty($title)): ?><h1 class="title" id="page-...
156                  title"><?php print $title; ?></h1><?php endif; ?>
157              <?php if (!empty($tabs)): ?><div class="tabs"><?php print ...
158                  $tabs; ?></div><?php endif; ?>
159              <?php if (!empty($messages)): print $messages; endif; ?>
160              <?php if (!empty($help)): print $help; endif; ?>
161          <div id="content-content" class="clear-block">
162              <?php print $content; ?>
163          </div> <!-- /content-content -->
164          <?php print $feed_icons; ?>
165      </div> <!-- /content -->

166      </div></div> <!-- /main-squeeze /main -->

167      <?php if (!empty($right)): ?>
168          <div id="sidebar-right" class="column sidebar">
169              <?php print $right; ?>
170          </div> <!-- /sidebar-right -->
171      <?php endif; ?>

172      </div> <!-- /container -->

173      <div id="footer-wrapper">
174          <div id="footer">
175              <?php print $footer_message; ?>
176              <?php if (!empty($footer)): print $footer; endif; ?>
177          </div> <!-- /footer -->
178      </div> <!-- /footer-wrapper -->

179      <?php print $closure; ?>

180      </div> <!-- /page -->

```

182 |
| </body>
| </html>

Capítulo 12

Carpetas drupal/modules/user

12.1. Fichero user-picture.tpl.php

```
1 <?php
// $Id: user-picture.tpl.php, v 1.2 2007/08/07 08:39:36 goba Exp $

/**
 * @file user-picture.tpl.php
 * Default theme implementation to present an picture configured for ...
 * the
 * user's account.
 *
 * Available variables:
 * - $picture: Image set by the user or the site's default. Will be ...
 * linked
11 * depending on the viewer's permission to view the users profile ...
 * page.
 * - $account: Array of account information. Potentially unsafe. Be ...
 * sure to
 * check_plain() before use.
 *
 * @see template_preprocess_user_picture()
16 */
?>
<div class="picture">
  <?php print $picture; ?>
</div>
```

12.2. Fichero user-profile-category.tpl.php

```
<?php
// $Id: user-profile-category.tpl.php, v 1.2 2007/08/07 08:39:36 goba ...
Exp $

/**
 * @file user-profile-category.tpl.php
 * Default theme implementation to present profile categories (groups ...
 * of
```

```

    * profile items).
    *
    * Categories are defined when configuring user profile fields for the...
    * site.
10   * It can also be defined by modules. All profile items for a category...
    * will be
    * output through the $profile_items variable.
    *
    * @see user-profile-item.tpl.php
    *      where each profile item is rendered. It is implemented as a ...
    *      definition
15   * list by default.
    * @see user-profile.tpl.php
    *      where all items and categories are collected and printed out.
    *
    * Available variables:
20   * - $title: Category title for the group of items.
    * - $profile_items: All the items for the group rendered through
    *      user-profile-item.tpl.php.
    * - $attributes: HTML attributes. Usually renders classes.
    *
25   * @see template_preprocess_user_profile_category()
    */
?>
<?php if ($title) : ?>
    <h3><?php print $title; ?></h3>
30 <?php endif; ?>

<dl><?php print $attributes; ?>>
    <?php print $profile_items; ?>
</dl>

```

12.3. Fichero user-profile-item.tpl.php

```

1  <?php
// $Id: user-profile-item.tpl.php,v 1.2 2007/08/07 08:39:36 goba Exp $

/**
 * @file user-profile-item.tpl.php
6   * Default theme implementation to present profile items (values from ...
    * user
    * account profile fields or modules).
    *
    * This template is used to loop through and render each field ...
    * configured
    * for the user's account. It can also be the data from modules. The ...
    * output is
11  * grouped by categories.
    *
    * @see user-profile-category.tpl.php
    *      for the parent markup. Implemented as a definition list by ...
    *      default.

```

```

16   * @see user-profile.tpl.php
16   *      where all items and categories are collected and printed out.
16   *
16   * Available variables:
16   * - $title: Field title for the profile item.
16   * - $value: User defined value for the profile item or data from a ...
16   *            module.
16   * - $attributes: HTML attributes. Usually renders classes.
16   *
16   * @see template_preprocess_user_profile_item()
16   */
16 ?>
26 <dt><?php print $attributes; ?><?php print $title; ?></dt>
26 <dd><?php print $attributes; ?><?php print $value; ?></dd>

```

12.4. Fichero user-profile.tpl.php

```

<?php
// $Id: user-profile.tpl.php, v 1.2.2.2 2009/10/06 11:50:06 goba Exp $
3
/**
 * @file user-profile.tpl.php
 * Default theme implementation to present all user profile data.
 *
8 * This template is used when viewing a registered member's profile ...
 * page,
 * e.g., example.com/user/123. 123 being the users ID.
 *
 * By default, all user profile data is printed out with the ...
 * $user_profile
 * variable. If there is a need to break it up you can use $profile ...
 * instead.
13 * It is keyed to the name of each category or other data attached to ...
 * the
 * account. If it is a category it will contain all the profile items....
 * By
 * default $profile['summary'] is provided which contains data on the ...
 * user's
 * history. Other data can be included by modules. $profile['...
 * user_picture'] is
 * available by default showing the account picture.
18 *
 * Also keep in mind that profile items and their categories can be ...
 * defined by
 * site administrators. They are also available within $profile. For ...
 * example,
 * if a site is configured with a category of "contact" with
 * fields for of addresses, phone numbers and other related info, then...
 * doing a
23 * straight print of $profile['contact'] will output everything in the
 * category. This is useful for altering source order and adding ...
 * custom

```

```
28 * markup for the group.  
*  
* To check for all available data within $profile, use the code below...  
* .  
* @code  
* print '<pre>'. check_plain(print_r($profile, 1)) . '</pre>';  
* @endcode  
*  
* Available variables:  
33 * - $user_profile: All user profile data. Ready for print.  
* - $profile: Keyed array of profile categories and their items or ...  
* other data  
* provided by modules.  
*  
* @see user-profile-category.tpl.php  
38 * Where the html is handled for the group.  
* @see user-profile-item.tpl.php  
* Where the html is handled for each item in the group.  
* @see template_preprocess_user_profile()  
*/  
43?>  
<div class="profile">  
    <?php print $user_profile; ?>  
</div>
```

Capítulo 13

Carpeta drupal/sites/default

13.1. Fichero default.settings.php

```
<?php
// $Id: default.settings.php, v 1.8.2.4 2009/09/14 12:59:18 goba Exp $
4 /**
 * @file
 * Drupal site-specific configuration file.
 *
 * IMPORTANT NOTE:
9 * This file may have been set to read-only by the Drupal installation
 * program. If you make changes to this file, be sure to protect it ...
 * again
 * after making your modifications. Failure to remove write ...
 * permissions
 * to this file is a security risk.
 *
14 * The configuration file to be loaded is based upon the rules below.
 *
 * The configuration directory will be discovered by stripping the
 * website's hostname from left to right and pathname from right to
 * left. The first configuration file found will be used and any
19 * others will be ignored. If no other configuration file is found
 * then the default configuration file at 'sites/default' will be used...
 *
 *
 * For example, for a fictitious site installed at
 * http://www.drupal.org/mysite/test/, the 'settings.php'
24 * is searched in the following directories:
 *
 * 1. sites/www.drupal.org.mysite.test
 * 2. sites/drupal.org.mysite.test
 * 3. sites/org.mysite.test
29 *
 * 4. sites/www.drupal.org.mysite
 * 5. sites/drupal.org.mysite
 * 6. sites/org.mysite
 *
34 * 7. sites/www.drupal.org
```

```

*   8. sites/drupal.org
*   9. sites/org
*
* 10. sites/default
39 *
* If you are installing on a non-standard port number, prefix the
* hostname with that number. For example,
* http://www.drupal.org:8080/mysite/test/ could be loaded from
* sites/8080.www.drupal.org.mysite.test/.
44 */

/***
* Database settings:
*
49 * Note that the $db_url variable gets parsed using PHP's built-in
* URL parser (i.e. using the "parse_url()" function) so make sure
* not to confuse the parser. If your username, password
* or database name contain characters used to delineate
* $db_url parts, you can escape them via URI hex encodings:
54 *
* : = %3a    / = %2f    @ = %40
* + = %2b    ( = %28    ) = %29
* ? = %3f    = = %3d    & = %26
*
59 * To specify multiple connections to be used in your site (i.e. for
* complex custom modules) you can also specify an associative array
* of $db_url variables with the 'default' element used until ...
* otherwise
* requested.
*
64 * You can optionally set prefixes for some or all database table ...
* names
* by using the $db_prefix setting. If a prefix is specified, the ...
* table
* name will be prepended with its value. Be sure to use valid ...
* database
* characters only, usually alphanumeric and underscore. If no ...
* prefixes
* are desired, leave it as an empty string ''.
69 *
* To have all database names prefixed, set $db_prefix as a string:
*
* $db_prefix = 'main_';
*
74 * To provide prefixes for specific tables, set $db_prefix as an array...
*
* The array's keys are the table names and the values are the ...
* prefixes.
* The 'default' element holds the prefix for any tables not specified
* elsewhere in the array. Example:
*
79 * $db_prefix = array(
*   'default' => 'main_',
*   'users'     => 'shared_',

```

```

84     *      'sessions' => 'shared_',
85     *      'role'      => 'shared_',
86     *      'authmap'   => 'shared_',
87     *      );
88
89     * Database URL format:
90     * $db_url = 'mysql://username:password@localhost/databasename';
91     * $db_url = 'mysqli://username:password@localhost/databasename';
92     * $db_url = 'pgsql://username:password@localhost/databasename';
93     */
94 $db_url = 'mysql://username:password@localhost/databasename';
95 $db_prefix = '';
96
97 /**
98 * Access control for update.php script
99 *
100 * If you are updating your Drupal installation using the update.php ...
101 * script
102 * being not logged in as administrator, you will need to modify the ...
103 * access
104 * check statement below. Change the FALSE to a TRUE to disable the ...
105 * access
106 * check. After finishing the upgrade, be sure to open this file again
107 * and change the TRUE back to a FALSE!
108 */
109 $update_free_access = FALSE;
110
111 /**
112 * Base URL (optional).
113 *
114 * If you are experiencing issues with different site domains,
115 * uncomment the Base URL statement below (remove the leading hash ...
116 * sign)
117 * and fill in the absolute URL to your Drupal installation.
118 *
119 * You might also want to force users to use a given domain.
120 * See the .htaccess file for more information.
121 *
122 * Examples:
123 * $base_url = 'http://www.example.com';
124 * $base_url = 'http://www.example.com:8888';
125 * $base_url = 'http://www.example.com/drupal';
126 * $base_url = 'https://www.example.com:8888/drupal';
127 *
128 * It is not allowed to have a trailing slash; Drupal will add it
129 * for you.
130 */
131 # $base_url = 'http://www.example.com'; // NO trailing slash!
132
133 /**
134 * PHP settings:
135 *
136 * To see what PHP settings are possible, including whether they can
137 * be set at runtime (ie., when ini_set() occurs), read the PHP

```

```

134  * documentation at http://www.php.net/manual/en/ini.php#ini.list
134  * and take a look at the .htaccess file to see which non-runtime
134  * settings are used there. Settings defined here should not be
134  * duplicated there so as to avoid conflict issues.
134  */
135 ini_set('arg_separator.output',      '&');
136 ini_set('magic_quotes_runtime',     0);
137 ini_set('magic_quotes_sybase',     0);
138 ini_set('session.cache_expire',    200000);
139 ini_set('session.cache_limiter',   'none');
140 ini_set('session.cookie_lifetime', 2000000);
141 ini_set('session.gc_maxlifetime',  200000);
142 ini_set('session.save_handler',    'user');
143 ini_set('session.use_cookies',    1);
144 ini_set('session.use_only_cookies', 1);
145 ini_set('session.use_trans_sid',  0);
146 ini_set('url_rewriter.tags',       '');
147
148 /**
149  * If you encounter a situation where users post a large amount of ...
149  * text, and
150  * the result is stripped out upon viewing but can still be edited, ...
150  * Drupal's
151  * output filter may not have sufficient memory to process it. If you
151  * experience this issue, you may wish to uncomment the following two ...
151  * lines
152  * and increase the limits of these variables. For more information, ...
152  * see
153  * http://php.net/manual/en/pcre.configuration.php.
153  */
154 # ini_set('pcre.backtrack_limit', 200000);
155 # ini_set('pcre.recursion_limit', 200000);
156
157 /**
158  * Drupal automatically generates a unique session cookie name for ...
158  * each site
159  * based on its full domain name. If you have multiple domains ...
159  * pointing at
160  * the same Drupal site, you can either redirect them all to a single ...
160  * domain
161  * (see comment in .htaccess), or uncomment the line below and specify...
161  * their
162  * shared base domain. Doing so assures that users remain logged in as...
162  * they
163  * cross between your various domains.
163  */
164 # $cookie_domain = 'example.com';
165
166 /**
167  * Variable overrides:
168  *
169  * To override specific entries in the 'variable' table for this site,
170  * set them here. You usually don't need to use this feature. This is

```

```

179      * useful in a configuration file for a vhost or directory, rather ...
      * than
      * the default settings.php. Any configuration setting from the '...
      * variable'
      * table can be given a new value. Note that any values you provide in
      * these variable overrides will not be modifiable from the Drupal
      * administration interface.
      *
      * Remove the leading hash signs to enable.
      */
184 # $conf = array(
#   'site_name' => 'My Drupal site',
#   'theme_default' => 'minnelli',
#   'anonymous' => 'Visitor',
/**/
189   * A custom theme can be set for the off-line page. This applies when ...
   * the site
   * is explicitly set to off-line mode through the administration page ...
   * or when
   * the database is inactive due to an error. It can be set through the
   * 'maintenance_theme' key. The template file should also be copied ...
   * into the
   * theme. It is located inside 'modules/system/maintenance-page.tpl...
   * php'.
194   * Note: This setting does not apply to installation and update pages.
   */
#   'maintenance_theme' => 'minnelli',
/**/
199   * reverse_proxy accepts a boolean value.
   *
   * Enable this setting to determine the correct IP address of the ...
   * remote
   * client by examining information stored in the X-Forwarded-For ...
   * headers.
   * X-Forwarded-For headers are a standard mechanism for identifying ...
   * client
   * systems connecting through a reverse proxy server, such as Squid or
204   * Pound. Reverse proxy servers are often used to enhance the ...
   * performance
   * of heavily visited sites and may also provide other site caching,
   * security or encryption benefits. If this Drupal installation ...
   * operates
   * behind a reverse proxy, this setting should be enabled so that ...
   * correct
   * IP address information is captured in Drupal's session management,
209   * logging, statistics and access management systems; if you are ...
   * unsure
   * about this setting, do not have a reverse proxy, or Drupal operates...
   * in
   * a shared hosting environment, this setting should be set to ...
   * disabled.
   */
#   'reverse_proxy' => TRUE,
214 /**

```

```

* reverse_proxy accepts an array of IP addresses.
*
* Each element of this array is the IP address of any of your reverse
* proxies. Filling this array Drupal will trust the information ...
* stored
219 * in the X-Forwarded-For headers only if Remote IP address is one of
* these, that is the request reaches the web server from one of your
* reverse proxies. Otherwise, the client could directly connect to
* your web server spoofing the X-Forwarded-For headers.
*/
224 # 'reverse_proxy_addresses' => array('a.b.c.d', ...),
# );

/**
* String overrides:
229 *
* To override specific strings on your site with or without enabling ...
* locale
* module, add an entry to this list. This functionality allows you to...
* change
* a small number of your site's default English language interface ...
* strings.
*
234 * Remove the leading hash signs to enable.
*/
#
# $conf['locale_custom_strings_en'] = array(
#   'forum' => 'Discussion board',
#   '@count min' => '@count minutes',
239 # );

```

13.2. Fichero settings.php

```

1 <?php
// $Id: default.settings.php, v 1.8.2.4 2009/09/14 12:59:18 goba Exp $

/*
* @file
6 * Drupal site-specific configuration file.
*
* IMPORTANT NOTE:
* This file may have been set to read-only by the Drupal installation
* program. If you make changes to this file, be sure to protect it ...
* again
11 * after making your modifications. Failure to remove write ...
* permissions
* to this file is a security risk.
*
* The configuration file to be loaded is based upon the rules below.
*
16 * The configuration directory will be discovered by stripping the
* website's hostname from left to right and pathname from right to
* left. The first configuration file found will be used and any

```

```

* others will be ignored. If no other configuration file is found
* then the default configuration file at 'sites/default' will be used...
*
21 *
* For example, for a fictitious site installed at
* http://www.drupal.org/mysite/test/, the 'settings.php'
* is searched in the following directories:
*
26 * 1. sites/www.drupal.org.mysite.test
* 2. sites/drupal.org.mysite.test
* 3. sites/org.mysite.test
*
* 4. sites/www.drupal.org.mysite
31 * 5. sites/drupal.org.mysite
* 6. sites/org.mysite
*
* 7. sites/www.drupal.org
* 8. sites/drupal.org
36 * 9. sites/org
*
* 10. sites/default
*
* If you are installing on a non-standard port number, prefix the
41 * hostname with that number. For example,
* http://www.drupal.org:8080/mysite/test/ could be loaded from
* sites/8080.www.drupal.org.mysite.test/.
*/
46 /**
* Database settings:
*
* Note that the $db_url variable gets parsed using PHP's built-in
* URL parser (i.e. using the "parse_url()" function) so make sure
51 * not to confuse the parser. If your username, password
* or database name contain characters used to delineate
* $db_url parts, you can escape them via URI hex encodings:
*
* : = %3a    / = %2f    @ = %40
* + = %2b    ( = %28    ) = %29
* ? = %3f    = = %3d    & = %26
*
* To specify multiple connections to be used in your site (i.e. for
* complex custom modules) you can also specify an associative array
61 * of $db_url variables with the 'default' element used until ...
* otherwise
* requested.
*
* You can optionally set prefixes for some or all database table ...
* names
* by using the $db_prefix setting. If a prefix is specified, the ...
* table
66 * name will be prepended with its value. Be sure to use valid ...
* database

```

```

* characters only, usually alphanumeric and underscore. If no ...
* prefixes
* are desired, leave it as an empty string ''.
*
* To have all database names prefixed, set $db_prefix as a string:
71 *
*   $db_prefix = 'main_';
*
* To provide prefixes for specific tables, set $db_prefix as an array...
*
* The array's keys are the table names and the values are the ...
* prefixes.
76 * The 'default' element holds the prefix for any tables not specified
* elsewhere in the array. Example:
*
*   $db_prefix = array(
*     'default' => 'main_',
81 *     'users'    => 'shared_',
*     'sessions'  => 'shared_',
*     'role'      => 'shared_',
*     'authmap'   => 'shared_',
*   );
86 *
* Database URL format:
*   $db_url = 'mysql://username:password@localhost/databasename';
*   $db_url = 'mysqli://username:password@localhost/databasename';
*   $db_url = 'pgsql://username:password@localhost/databasename';
91 */
$db_url = 'mysql://root@localhost/drupal';
$db_prefix = '';

/**/
96 * Access control for update.php script
*
* If you are updating your Drupal installation using the update.php ...
* script
* being not logged in as administrator, you will need to modify the ...
* access
* check statement below. Change the FALSE to a TRUE to disable the ...
* access
101 * check. After finishing the upgrade, be sure to open this file again
* and change the TRUE back to a FALSE!
*/
$update_free_access = FALSE;

106 /**
* Base URL (optional).
*
* If you are experiencing issues with different site domains,
* uncomment the Base URL statement below (remove the leading hash ...
* sign)
111 * and fill in the absolute URL to your Drupal installation.
*
* You might also want to force users to use a given domain.

```

```

    * See the .htaccess file for more information.
    *
116   * Examples:
    * $base_url = 'http://www.example.com';
    * $base_url = 'http://www.example.com:8888';
    * $base_url = 'http://www.example.com/drupal';
    * $base_url = 'https://www.example.com:8888/drupal';
121   *
    * It is not allowed to have a trailing slash; Drupal will add it
    * for you.
    */
# $base_url = 'http://www.example.com'; // NO trailing slash!

126 /**
    * PHP settings:
    *
    * To see what PHP settings are possible, including whether they can
131   * be set at runtime (ie., when ini_set() occurs), read the PHP
    * documentation at http://www.php.net/manual/en/ini.php#ini.list
    * and take a look at the .htaccess file to see which non-runtime
    * settings are used there. Settings defined here should not be
    * duplicated there so as to avoid conflict issues.
136 */
ini_set('arg_separator.output', '&');
ini_set('magic_quotes_runtime', 0);
ini_set('magic_quotes_sybase', 0);
ini_set('session.cache_expire', 200000);
141 ini_set('session.cache_limiter', 'none');
ini_set('session.cookie_lifetime', 2000000);
ini_set('session.gc_maxlifetime', 200000);
ini_set('session.save_handler', 'user');
ini_set('session.use_cookies', 1);
146 ini_set('session.use_only_cookies', 1);
ini_set('session.use_trans_sid', 0);
ini_set('url_rewriter.tags', '');

/**
151 * If you encounter a situation where users post a large amount of ...
    * text, and
    * the result is stripped out upon viewing but can still be edited, ...
    * Drupal's
    * output filter may not have sufficient memory to process it. If you
    * experience this issue, you may wish to uncomment the following two ...
    * lines
    * and increase the limits of these variables. For more information, ...
    * see
156 * http://php.net/manual/en/pcre.configuration.php.
    */
# ini_set('pcre.backtrack_limit', 200000);
# ini_set('pcre.recursion_limit', 200000);

161 /**
    * Drupal automatically generates a unique session cookie name for ...
    * each site

```

```

    * based on on its full domain name. If you have multiple domains ...
    * pointing at
    * the same Drupal site , you can either redirect them all to a single ...
    * domain
    * (see comment in .htaccess), or uncomment the line below and specify...
    * their
166   * shared base domain. Doing so assures that users remain logged in as...
    * they
    * cross between your various domains.
    */
# $cookie_domain = 'example.com';

171 /**
 * Variable overrides :
 *
 * To override specific entries in the 'variable' table for this site ,
 * set them here. You usually don't need to use this feature. This is
176   * useful in a configuration file for a vhost or directory , rather ...
    * than
    * the default settings.php . Any configuration setting from the '...
    * variable'
    * table can be given a new value. Note that any values you provide in
    * these variable overrides will not be modifiable from the Drupal
    * administration interface .
181   *
    * Remove the leading hash signs to enable .
    */
# $conf = array(
#   'site_name' => 'My Drupal site',
#   'theme_default' => 'minnelli',
#   'anonymous' => 'Visitor',
/* A custom theme can be set for the off-line page. This applies when ...
   the site
   * is explicitly set to off-line mode through the administration page ...
   * or when
191   * the database is inactive due to an error. It can be set through the
   * 'maintenance_theme' key. The template file should also be copied ...
   * into the
   * theme. It is located inside 'modules/system/maintenance-page.tpl....
   * php'.
   * Note: This setting does not apply to installation and update pages.
   */
#   'maintenance_theme' => 'minnelli',
/** reverse_proxy accepts a boolean value .
 *
 * Enable this setting to determine the correct IP address of the ...
   remote
201   * client by examining information stored in the X-Forwarded-For ...
   * headers .
   * X-Forwarded-For headers are a standard mechanism for identifying ...
   * client
   * systems connecting through a reverse proxy server , such as Squid or

```

```

206    * Pound. Reverse proxy servers are often used to enhance the ...
    * performance
    * of heavily visited sites and may also provide other site caching,
206  * security or encryption benefits. If this Drupal installation ...
    * operates
    * behind a reverse proxy, this setting should be enabled so that ...
    * correct
    * IP address information is captured in Drupal's session management,
    * logging, statistics and access management systems; if you are ...
    * unsure
    * about this setting, do not have a reverse proxy, or Drupal operates...
    * in
211  * a shared hosting environment, this setting should be set to ...
    * disabled.
*/
# 'reverse_proxy' => TRUE,
/** *
 * reverse_proxy accepts an array of IP addresses.
216  *
 * Each element of this array is the IP address of any of your reverse
 * proxies. Filling this array Drupal will trust the information ...
    * stored
    * in the X-Forwarded-For headers only if Remote IP address is one of
    * these, that is the request reaches the web server from one of your
221  * reverse proxies. Otherwise, the client could directly connect to
    * your web server spoofing the X-Forwarded-For headers.
*/
# 'reverse_proxy_addresses' => array('a.b.c.d', ...),
# );
226 /**
 * String overrides:
 *
 * To override specific strings on your site with or without enabling ...
    * locale
231  * module, add an entry to this list. This functionality allows you to...
    * change
    * a small number of your site's default English language interface ...
    * strings.
 *
 * Remove the leading hash signs to enable.
*/
# $conf['locale_custom_strings_en'] = array(
#   'forum'      => 'Discussion board',
#   '@count min' => '@count minutes',
# );

```

Capítulo 14

Carpeta drupal/themes/bluemarine

14.1. Fichero block.tpl.php

```
1 <?php
// $Id: block.tpl.php, v 1.3 2007/08/07 08:39:36 gobal Exp $
?>
<div class="block block-<?php print $block->module; ?>" id="block-<?...
    php print $block->module; ?>-<?php print $block->delta; ?>">
        <h2 class="title"><?php print $block->subject; ?></h2>
            <div class="content"><?php print $block->content; ?></div>
    </div>
```

14.2. Fichero box.tpl.php

```
1 <?php
// $Id: box.tpl.php, v 1.3 2007/08/07 08:39:36 gobal Exp $
?>
<div class="box">
    <?php if ($title) { ?><h2 class="title"><?php print $title; ?></h2...
        ><?php } ?>
        <div class="content"><?php print $content; ?></div>
    </div>
```

14.3. Fichero comment.tpl.php

```
1 <?php
// $Id: comment.tpl.php, v 1.7 2008/01/04 19:24:23 gobal Exp $
?>
<div class="comment<?php print ' '. $status; ?>">
    <?php if ($picture) {
        print $picture;
    } ?>
```

```

<h3 class="title"><?php print $title; ?></h3><?php if ($new != '') { ...
?><span class="new"><?php print $new; ?></span><?php } ?>
<div class="submitted"><?php print $submitted; ?></div>
<div class="content">
<?php print $content; ?>
<?php if ($signature): ?>
<div class="clear-block">
<div> </div>
<?php print $signature ?>
</div>
<?php endif; ?>
</div>
<div class="links">&raquo; <?php print $links; ?></div>
</div>

```

14.4. Fichero node.tpl.php

```

<?php
// $Id: node.tpl.php, v 1.7 2007/08/07 08:39:36 goba Exp $
?>
<div class="node"><?php if ($sticky) { print " sticky"; } ?><?php if ...
(!$status) { print " node-unpublished"; } ?>">
<?php if ($picture) {
  print $picture;
}>
<?php if ($page == 0) { ?><h2 class="title"><a href=<?php print ...
$node_url?>"><?php print $title?></a></h2><?php }; ?>
<span class="submitted"><?php print $submitted?></span>
<div class="taxonomy"><?php print $terms?></div>
<div class="content"><?php print $content?></div>
<?php if ($links) { ?><div class="links">&raquo; <?php print ...
$links?></div><?php }; ?>
</div>

```

14.5. Fichero page.tpl.php

```

<?php
// $Id: page.tpl.php, v 1.28.2.1 2009/04/30 00:13:31 goba Exp $
?><!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN" "http://www...
.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" lang=<?php print $language...
->language ?>" xml:lang=<?php print $language->language ?>" dir="...
<?php print $language->dir ?>">

<head>
<?php print $head ?>
<title><?php print $head_title ?></title>
<?php print $styles ?>
<?php print $scripts ?>

```

```

12 <script type="text/javascript"><?php /* Needed to avoid Flash of ...
   Unstyle Content in IE */ ?> </script>
</head>

<body>

<table border="0" cellpadding="0" cellspacing="0" id="header">
17  <tr>
    <td id="logo">
        <?php if ($logo) { ?><a href="php print $front_page ?&gt;" title=...
" &lt;?php print t('Home') ?&gt;"<?php print...
$site_name ?></a></h1><?php } ?>
        <?php if ($site_slogan) { ?><div class='site-slogan'><?php print...
$site_slogan ?></div><?php } ?>
22  </td>
    <td id="menu">
        <?php if (isset($secondary_links)) { ?><?php print theme('links',...
, $secondary_links, array('class' => 'links', 'id' => 'subnavlist',...
)) ?><?php } ?>
        <?php if (isset($primary_links)) { ?><?php print theme('links',...
$primary_links, array('class' => 'links', 'id' => 'navlist')) ?><?...
php } ?>
        <?php print $search_box ?>
27  </td>
</tr>
<tr>
    <td colspan="2"><div><?php print $header ?></div></td>
</tr>
32  </table>

<table border="0" cellpadding="0" cellspacing="0" id="content">
<tr>
    <?php if ($left) { ?><td id="sidebar-left">
37  <?php print $left ?>
    </td><?php } ?>
    <td valign="top">
        <?php if ($mission) { ?><div id="mission"><?php print $mission ...
?></div><?php } ?>
        <div id="main">
            <?php print $breadcrumb ?>
            <h1 class="title"><?php print $title ?></h1>
            <div class="tabs"><?php print $tabs ?></div>
            <?php if ($show_messages) { print $messages; } ?>
            <?php print $help ?>
47  <?php print $content; ?>
            <?php print $feed_icons; ?>
        </div>
    </td>
    <?php if ($right) { ?><td id="sidebar-right">
52  <?php print $right ?>
    </td><?php } ?>

```

```
        </tr>
</table>

57 <div id="footer">
    <?php print $footer_message ?>
    <?php print $footer ?>
</div>
<?php print $closure ?>
62 </body>
</html>
```

Capítulo 15

Carpeta drupal/themes/garland

15.1. Fichero block.tpl.php

```
<?php
// $Id: block.tpl.php, v 1.3 2007/08/07 08:39:36 gobal_Exp $
?>
<div id="block-<?php print $block->module . '-' . $block->delta; ?>" ...
    class="clear-block block block-<?php print $block->module ?>">

<?php if (!empty($block->subject)) : ?>
    <h2><?php print $block->subject ?></h2>
<?php endif;?>

    <div class="content"><?php print $block->content ?></div>
</div>
```

15.2. Fichero comment.tpl.php

```
<?php
// $Id: comment.tpl.php, v 1.10 2008/01/04 19:24:24 gobal_Exp $
?>
<div class="comment<?php print ($comment->new) ? ' comment-new' : ''; ...
    print ' '. $status; print ' '. $zebra; ?>">

    <div class="clear-block">
        <?php if ($submitted) : ?>
            <span class="submitted"><?php print $submitted; ?></span>
        <?php endif; ?>

        <?php if ($comment->new) : ?>
            <span class="new"><?php print drupal_ucfirst($new) ?></span>
        <?php endif; ?>
    <?php print $picture ?>
```

```

19   <h3><?php print $title ?></h3>
20
21   <div class="content">
22     <?php print $content ?>
23     <?php if ($signature): ?>
24       <div class="clear-block">
25         <div>    </div>
26         <?php print $signature ?>
27       </div>
28       <?php endif; ?>
29     </div>
30
31   <?php if ($links): ?>
32     <div class="links"><?php print $links ?></div>
33   <?php endif; ?>
34
35 </div>

```

15.3. Fichero maintenance-page.tpl.php

```

<?php
// $Id: maintenance-page.tpl.php, v 1.3.2.1 2009/04/30 00:13:31 goba ...
Exp $

/**
 * @file maintenance-page.tpl.php
 *
7 * This is an override of the default maintenance page. Used for ...
 * Garland and
 * Minnelli, this file should not be moved or modified since the ...
 * installation
 * and update pages depend on this file.
 *
 * This mirrors closely page.tpl.php for Garland in order to share the...
 * same
12 * styles.
 */
?><!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict //EN"
 "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="<?php print ...
    $language->language ?>" lang="<?php print $language->language ?>" ...
    dir="<?php print $language->dir ?>">
<head>
    <?php print $head ?>
    <title><?php print $head_title ?></title>
    <?php print $styles ?>
    <?php print $scripts ?>
22    <!--[if lt IE 7]>
        <?php print phptemplate_get_ie_styles(); ?>
        <![endif]-->
    </head>
<body><?php print phptemplate_body_class($left, $right); ?>>

```

```

27 |<!-- Layout -->
28 |<div id="header-region" class="clear-block"><?php print $header; ...?
29 |?></div>
30 |
31 |<div id="wrapper">
32 |<div id="container" class="clear-block">
33 |
34 |<div id="header">
35 |<div id="logo-floater">
36 |<?php
37 |    // Prepare header
38 |    $site_fields = array();
39 |    if ($site_name) {
40 |        $site_fields[] = check_plain($site_name);
41 |    }
42 |    if ($site_slogan) {
43 |        $site_fields[] = check_plain($site_slogan);
44 |    }
45 |    $site_title = implode(' ', $site_fields);
46 |    if ($site_fields) {
47 |        $site_fields[0] = '<span>' . $site_fields[0] . '</span>';
48 |    }
49 |    $site_html = implode(' ', $site_fields);
50 |
51 |    if ($logo || $site_title) {
52 |        print '<h1><a href="'. check_url($base_path) .'" title="'. ...
53 |$site_title .'">';
54 |        if ($logo) {
55 |            print '';
57 |        }
58 |        print $site_html . '</a></h1>';
59 |    }
60 |?>
61 |</div>
62 |</div> <!-- /header -->
63 |
64 |<?php if ($left): ?>
65 |<div id="sidebar-left" class="sidebar">
66 |<?php if ($search_box): ?><div class="block block-theme"><?...
67 |php print $search_box ?></div><?php endif; ?>
68 |<?php print $left ?>
69 |</div>
70 |<?php endif; ?>
71 |
72 |<div id="center"><div id="squeeze"><div class="right-corner"><...
73 |div class="left-corner">
74 |<?php if ($title): print '<h2>'. ($tabs ? ' class="with-tabs"...
75 |' : '') . '>'. $title . '</h2>'; endif; ?>
76 |<?php print $help; ?>
77 |<?php print $messages; ?>
78 |<div class="clear-block">

```

```

    <?php print $content ?>
</div>
77  <div id="footer"><?php print $footer_message . $footer ?><!-- /left-corner, /right-corner, /#...
    </div></div></div> <!-- /center -->

    <?php if ($right) : ?>
82   <div id="sidebar-right" class="sidebar">
      <?php print $right ?>
    </div>
    <?php endif; ?>

    </div> <!-- /container -->
87  </div>
<!-- /layout -->

</body>
</html>
```

15.4. Fichero node.tpl.php

```

<?php
// $Id: node.tpl.php, v 1.5 2007/10/11 09:51:29 goba Exp $
?>
4 <div id="node-<?php print $node->nid; ?>" class="node<?php if ($sticky...>
    ) { print ' sticky'; } ?><?php if (!$status) { print ' node-...>
    unpublished'; } ?>">

<?php print $picture ?>

<?php if ($page == 0) : ?>
9   <h2><a href=<?php print $node_url ?>" title=<?php print $title ?>"><?php print $title ?></a></h2>
<?php endif; ?>

<?php if ($submitted) : ?>
14   <span class="submitted"><?php print $submitted; ?></span>
<?php endif; ?>

<div class="content clear-block">
    <?php print $content ?>
</div>

19 <div class="clear-block">
    <div class="meta">
        <?php if ($taxonomy) : ?>
            <div class="terms"><?php print $terms ?></div>
24        <?php endif; ?>
    </div>

    <?php if ($links) : ?>
```

```

29      <div class="links"><?php print $links; ?></div>
     <?php endif; ?>
</div>

</div>

```

15.5. Fichero page.tpl.php

```

<?php
// $Id: page.tpl.php , v 1.18.2.1 2009/04/30 00:13:31 goba Exp $ 
?><!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
 "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="<?php print ...
    $language->language ?>" lang="<?php print $language->language ?>" ...
    dir="<?php print $language->dir ?>">
<head>
    <?php print $head ?>
8     <title><?php print $head_title ?></title>
    <?php print $styles ?>
    <?php print $scripts ?>
    <!--[if lt IE 7]>
        <?php print phptemplate_get_ie_styles(); ?>
    <![endif]-->
13    </head>
<body><?php print phptemplate_body_class($left, $right); ?>>

<!-- Layout -->
18    <div id="header-region" class="clear-block"><?php print $header; ...
    ?></div>

    <div id="wrapper">
        <div id="container" class="clear-block">

            <div id="header">
                <div id="logo-floater">
                    <?php
                        // Prepare header
                        $site_fields = array();
28                        if ($site_name) {
                            $site_fields[] = check_plain($site_name);
                        }
                        if ($site_slogan) {
                            $site_fields[] = check_plain($site_slogan);
                        }
                        $site_title = implode(' ', $site_fields);
                        if ($site_fields) {
                            $site_fields[0] = '<span>' . $site_fields[0] . '</span>';
                        }
                        $site_html = implode(' ', $site_fields);
38                        if ($logo || $site_title) {

```

```

        print '<h1><a href="'. check_url($front_page) .'" title="...';
43     . $site_title . '"';
        if ($logo) {
            print '';
        }
        print $site_html . '</a></h1>';
    }
?>
48 </div>

<?php if (isset($primary_links)) : ?>
    <?php print theme('links', $primary_links, array('class' => ...
'links primary-links')) ?>
    <?php endif; ?>
    <?php if (isset($secondary_links)) : ?>
        <?php print theme('links', $secondary_links, array('class' ...
=> 'links secondary-links')) ?>
        <?php endif; ?>
53
</div> <!-- /header -->
58
<?php if ($left): ?>
    <div id="sidebar-left" class="sidebar">
        <?php if ($search_box): ?><div class="block block-theme"><?...
php print $search_box ?></div><?php endif; ?>
        <?php print $left ?>
63 </div>
<?php endif; ?>

<div id="center"><div id="squeeze"><div class="right-corner"><...
div class="left-corner">
    <?php print $breadcrumb; ?>
    <?php if ($mission): print '<div id="mission">'. $mission . ...
68 </div>; endif; ?>
    <?php if ($tabs): print '<div id="tabs-wrapper" class="clear ...
-block">'; endif; ?>
        <?php if ($title): print '<h2'. ($tabs ? ' class="with-tabs"...
' : '') . '>'. $title . '</h2>'; endif; ?>
        <?php if ($tabs): print '<ul class="tabs primary">'. $tabs ....
'</ul></div>; endif; ?>
        <?php if ($tabs2): print '<ul class="tabs secondary">'. ...
$tabs2 . '</ul>'; endif; ?>
        <?php if ($show_messages && $messages): print $messages; ...
73 endif; ?>
        <?php print $help; ?>
        <div class="clear-block">
            <?php print $content ?>
        </div>
        <?php print $feed_icons ?>
        <div id="footer"><?php print $footer_message . $footer ?><...
div>
        </div></div></div></div> <!-- /.left-corner, /.right-corner, /#...
squeeze, #center -->
78

```

```

83      <?php if ($right): ?>
84          <div id="sidebar-right" class="sidebar">
85              <?php if (!$left && $search_box): ?><div class="block block-...
86                  theme"><?php print $search_box ?></div><?php endif; ?>
87                  <?php print $right ?>
88          </div>
89      <?php endif; ?>
90
91      </div> <!-- /container -->
92      </div>
93      <!-- /layout -->
94
95      <?php print $closure ?>
96      </body>
97  </html>

```

15.6. Fichero template.php

```

<?php
// $Id: template.php , v 1.16.2.2 2009/08/10 11:32:54 goba Exp $

/**
 * Sets the body-tag class attribute.
 *
 * Adds 'sidebar-left', 'sidebar-right' or 'sidebars' classes as ...
 * needed.
 */
function phptemplate_body_class($left, $right) {
10    if ($left != '' && $right != '') {
11        $class = 'sidebars';
12    }
13    else {
14        if ($left != '') {
15            $class = 'sidebar-left';
16        }
17        if ($right != '') {
18            $class = 'sidebar-right';
19        }
20    }
21
22    if (isset($class)) {
23        print ' class="'. $class .'"';
24    }
25}

/**
 * Return a themed breadcrumb trail.
 *
30 * @param $breadcrumb
 * An array containing the breadcrumb links.
 * @return a string containing the breadcrumb output.

```

```

  */
35 function phptemplate_breadcrumb($breadcrumb) {
  if (!empty($breadcrumb)) {
    return '<div class="breadcrumb">' . implode(' ', $breadcrumb) . ...
    '</div>';
  }
}

40 /**
 * Override or insert PHPTemplate variables into the templates.
 */
function phptemplate_preprocess_page(&$vars) {
  $vars['tabs2'] = menu_secondary_local_tasks();
45
  // Hook into color.module
  if (module_exists('color')) {
    _color_page_alter($vars);
  }
50 }

/**
 * Add a "Comments" heading above comments except on forum pages.
 */
55 function garland_preprocess_comment_wrapper(&$vars) {
  if ($vars['content'] && $vars['node']->type != 'forum') {
    $vars['content'] = '<h2 class="comments">' . t('Comments') . '</h2>' ...
      . $vars['content'];
  }
}
60

/**
 * Returns the rendered local tasks. The default implementation ...
   renders
 * them as tabs. Overridden to split the secondary tasks.
 *
65 * @ingroup themeable
 */
function phptemplate_menu_local_tasks() {
  return menu_primary_local_tasks();
}
70

function phptemplate_comment_submitted($comment) {
  return t('!datetime !username',
  array(
    '!username' => theme('username', $comment),
75    '!datetime' => format_date($comment->tstamp)
  )));
}

80 function phptemplate_node_submitted($node) {
  return t('!datetime !username',
  array(
    '!username' => theme('username', $node),
    '!datetime' => format_date($node->created),
  ));
}

```

```
85     ));  
86 }  
  
87 /**  
 * Generates IE CSS links for LTR and RTL languages.  
 */  
88 function phptemplate_get_ie_styles() {  
89     global $language;  
  
90     $iecss = '<link type="text/css" rel="stylesheet" media="all" href="...  
91         .base_path() . path_to_theme() . "/fix-ie.css" />';  
92     if ($language->direction == LANGUAGE_RTL) {  
93         $iecss .= '<style type="text/css" media="all">@import "...  
94         .base_path() . path_to_theme() . "/fix-ie-rtl.css";</style>';  
95     }  
96     return $iecss;  
97 }
```

Capítulo 16

Carpeta drupal/themes/pushbutton

16.1. Fichero block.tpl.php

```
1 <?php
// $Id: block.tpl.php, v 1.2 2007/08/07 08:39:36 gobal Exp $
?>
<div class="block"><?php print "block block-$block->module" ?>" id="<?php ...
    print "block-$block->module-$block->delta"; ?>">
        <div class="title"><h3><?php print $block->subject ?></h3></div>
        <div class="content"><?php print $block->content ?></div>
    </div>
```

16.2. Fichero box.tpl.php

```
1 <?php
// $Id: box.tpl.php, v 1.3 2007/08/07 08:39:36 gobal Exp $
?>
<div class="box">
    <?php if ($title): ?>
        <h2 class="title"><?php print $title ?></h2>
    <?php endif; ?>
    <div class="content"><?php print $content ?></div>
</div>
```

16.3. Fichero comment.tpl.php

```
1 <?php
// $Id: comment.tpl.php, v 1.6 2008/01/04 19:24:24 gobal Exp $
?>
<div class="comment"><?php print ' ', $status; ?>">
    <?php if ($picture) : ?>
        <?php print $picture ?>
    <?php endif; ?>
```

```

<h3 class="title"><?php print $title ?></h3>
<div class="submitted"><?php print $submitted ?><?php if ($comment->...
  new) : ?><span class="new"> *<?php print $new ?></span><?php endif...
  ; ?></div>
<div class="content">
  <?php print $content ?>
  <?php if ($signature): ?>
    <div class="clear-block">
      <div> </div>
      <?php print $signature ?>
    </div>
    <?php endif; ?>
  </div>
  <!-- BEGIN: links -->
  <div class="links">&raquo; <?php print $links ?></div>
  <!-- END: links -->
</div>

```

16.4. Fichero node.tpl.php

```

<?php
// $Id: node.tpl.php, v 1.4 2007/08/07 08:39:36 goba Exp $
?>
<div class="node<?php if ($sticky) { print " sticky"; } ?><?php if (!...
  $status) { print " node-unpublished"; } ?>">
  <?php print $picture ?>
  <?php if ($page == 0): ?>
    <h1 class="title"><a href=<?php print $node_url ?>"><?php print ...
      $title ?></a></h1>
  <?php endif; ?>
  <span class="submitted"><?php print $submitted ?></span>
  <div class="taxonomy"><?php print $terms ?></div>
  <div class="content"><?php print $content ?></div>
  <?php if ($links): ?>
    <div class="links">&raquo; <?php print $links ?></div>
    <?php endif; ?>
</div>

```

16.5. Fichero page.tpl.php

```

<?php
// $Id: page.tpl.php, v 1.25.2.2 2009/04/30 00:13:31 goba Exp $
?><!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http...
  ://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" lang="<?php print $language...
  ->language ?>" xml:lang="<?php print $language->language ?>" dir="...
  <?php print $language->dir ?>">
<head>
  <meta http-equiv="Content-Type" content="text/css" />

```

```

10  <?php print $head ?>
<title><?php print $head_title ?></title>
<?php print $styles ?>
<?php print $scripts ?>
</head>

<body>

15 <div class="hide"><a href="#content" title=<?php print t('Skip ...
navigation') ?>.<?php print t('Skip navigation') ?></a>.</div>

<table id="primary-menu" summary="Navigation elements." border="0" ...
cellpadding="0" cellspacing="0" width="100 %">
<tr>
<td id="home" width="10 %">
<?php if ($logo) : ?>
    <a href=<?php print $front_page ?>" title=<?php print t('...
Home') ?>"><img src=<?php print($logo) ?>" alt=<?php print t('...
Home') ?>" border="0" /></a>
    <?php endif; ?>
</td>

20 <td id="site-info" width="20 %">
<?php if ($site_name) : ?>
    <div class='site-name'><a href=<?php print $front_page ?>" ...
title=<?php print t('Home') ?>"><?php print($site_name) ?></a><...>
    <?php endif; ?>
    <?php if ($site_slogan) : ?>
        <div class='site-slogan'><?php print($site_slogan) ?></div>
        <?php endif; ?>
    </td>
    <td class="primary-links" width="70 %" align="center" valign="...>
        <?php print theme('links', $primary_links, array('class' => '...
links', 'id' => 'navlist')) ?>
    </td>
</tr>
</table>

25 <table id="secondary-menu" summary="Navigation elements." border="0" ...
cellpadding="0" cellspacing="0" width="100 %">
<tr>
<td class="secondary-links" width="75 %" align="center" valign="...>
    <?php print theme('links', $secondary_links, array('class' => '...
links', 'id' => 'subnavlist')) ?>
    </td>
    <td width="25 %" align="center" valign="middle">
        <?php print $search_box ?>
    </td>
</tr>
<tr>

```

```
50    <td colspan="2"><div><?php print $header ?></div></td>
51    </tr>
52  </table>

53  <table id="content" border="0" cellpadding="15" cellspacing="0" width="100 %">
54    <tr>
55      <?php if ($left != "") : ?>
56      <td id="sidebar-left">
57        <?php print $left ?>
58      </td>
59      <?php endif; ?>

60      <td valign="top">
61        <?php if ($mission != "") : ?>
62        <div id="mission"><?php print $mission ?></div>
63        <?php endif; ?>

64        <div id="main">
65          <?php if ($title != "") : ?>
66          <?php print $breadcrumb ?>
67          <h1 class="title"><?php print $title ?></h1>
68
69          <?php if ($tabs != "") : ?>
70          <div class="tabs"><?php print $tabs ?></div>
71          <?php endif; ?>

72          <?php endif; ?>

73          <?php if ($show_messages && $messages != "") : ?>
74            <?php print $messages ?>
75          <?php endif; ?>

76          <?php if ($help != "") : ?>
77            <div id="help"><?php print $help ?></div>
78          <?php endif; ?>

79          <!-- start main content -->
80          <?php print $content; ?>
81          <?php print $feed_icons; ?>
82          <!-- end main content -->

83          </div><!-- main -->
84        </td>
85        <?php if ($right != "") : ?>
86        <td id="sidebar-right">
87          <?php print $right ?>
88        </td>
89        <?php endif; ?>
90      </tr>
91    </table>

92  <table id="footer-menu" summary="Navigation elements." border="0" ...
93    cellpadding="0" cellspacing="0" width="100 %">
```

```
105    <tr>
106      <td align="center" valign="middle">
107        <?php if (isset($primary_links)) : ?>
108          <?php print theme('links', $primary_links, array('class' => '...
109            links primary-links')) ?>
110        <?php endif; ?>
111        <?php if (isset($secondary_links)) : ?>
112          <?php print theme('links', $secondary_links, array('class' => '...
113            links secondary-links')) ?>
114        <?php endif; ?>
115      </td>
116    </tr>
117  </table>
118
119  <?php if ($footer_message || $footer) : ?>
120  <div id="footer-message">
121    <?php print $footer_message . $footer;?>
122  </div>
123  <?php endif; ?>
124  <?php print $closure;?>
125  </body>
126</html>
```

